

ME301YP

30-INCH SINGLE BUILT-IN OVEN

MASTERPIECE® COLLECTION WITH PROFESSIONAL HANDLE



FEATURES & BENEFITS

- WiFi smart appliance capabilities include personalized control, notifications & remote diagnostics via Home Connect® app
- Features 11 heating modes with 1 Full Access® telescopic rack
- Convection multi-rack mode gives uniform baking results even when using all 3 racks simultaneously
- SoftClose® hinges prevent slamming and ensure ultra-smooth closing
- Self-clean mode cleans interior walls and rack supports in as little as 2 hours



GENERAL PROPERTIES

Heating Modes

(11) Bake, Variable Broil (hi & low), Roast, Warm, Proof Dough, Convection Bake, Convection Broil, Convection Roast, Pizza, True Convection, Fast Preheat

| | |
|-------------------------------|------------|
| Sabbath | Yes |
| Cleaning Type | Self Clean |
| Telescopic Rack(s) | 1 |
| Standard Racks | 2 |
| Interior Lights | 2 Halogen |
| Home Connect® (Wi-Fi Enabled) | Yes |

OVEN PERFORMANCE

| | |
|--------------------|---------------------|
| Bake Element | 2,400 W (4 Passes) |
| Broil Element | 3,800 W (12 Passes) |
| Convection Element | 2,000 W |

TECHNICAL DETAILS

| | |
|---------------------|---------------------------|
| Watts (240 / 208 V) | 6,400 / 4,388 W |
| Circuit Breaker | 30 Amp |
| Volts | 240 / 208 V |
| Frequency | 60 Hz |
| Plug Type | Fixed Connection, No Plug |
| Conduit | 60" 4-Wire |
| Energy Source | Electric |

DIMENSIONS & WEIGHT

| | |
|--|-----------------------------------|
| Overall Appliance Dimensions (HxWxD) | 29" x 29 3/4" x 24 1/2" |
| Trim Overlaps (Top – Sides – Bottom) | 3/8" to 2" – 9/16" – 0" |
| Required Cutout Size (HxWxD) – Standard | 27" – 28 5/8" x 28 1/2" x 23 1/2" |
| Required Cutout Size (HxWxD) – Flush | 29 1/8" x 30" x 24 1/2" |
| Oven Cavity Size | 4.6 cu. ft. |
| Overall Oven Interior Dimensions (HxWxD) | 17 13/16" x 24 1/8" x 17 13/16" |
| Usable Oven Interior Dimensions (HxWxD) | 12 5/16" x 23 1/4" x 15 1/4" |
| Net Weight | 166 lbs |

ACCESSORIES (INCLUDED)

1 Telescopic and 2 Standard Oven Racks

WARRANTY

| | |
|----------------------------------|--------|
| Limited Warranty Parts and Labor | 2 Year |
|----------------------------------|--------|

†To be fully ADA compliant, these units must be installed according to ADA guidelines. Please check current ADA requirements for guidance on installation.

ME301YP

30-INCH SINGLE BUILT-IN OVEN

MASTERPIECE® COLLECTION WITH PROFESSIONAL HANDLE



INSTALLATION DETAILS

Single Oven Bottom Hinge

measurements in inches (mm)

Single Oven Wall Mount Installation

Dimensions for Under-Counter Installation

* Includes 3/4" (19 mm) base plate.
 ** For single ovens installed under a cabinet, the junction box should be located to the right or left of the unit within reach of the power cord.

measurements in inches (mm)

* For single ovens installed into a wall cabinet, the junction box may be located above, beneath, left or right of the unit within reach of the power cord.
 ** For oven installation in a wall cabinet, the control panel overlap is a min. 3/8" (10 mm) to max. 2" (51 mm).

measurements in inches (mm)

Flush Install Top View

Side View

measurements in inches (mm)

ME301YP

30-INCH SINGLE BUILT-IN OVEN

MASTERPIECE® COLLECTION WITH PROFESSIONAL HANDLE



INSTALLATION DETAILS

Standard installation
Single oven, double oven or combo oven over warming or storage drawer

28 1/2" (724 mm)

23 1/2" (597 mm)

Single oven, double oven or combo oven cut-out height

9 1/4" (235 mm)

min. 4 3/4" max. 18" (121-457 mm)

Minimum 3/4" (18 mm) required between cut-outs.

* Wall oven junction box may be located above or to the right or left of the unit within reach of the power cable.

** Electrical hook-up may be located below (depending on space) or next to the drawer within reach of the power cable.

measurements in inches (mm)

Flush installation
Single oven over storage or warming drawer

Side View

1" (25 mm)

Cleats

Single oven cut-out height

9 9/16" (243 mm) flush cutout height

**24 1/2" (622 mm)

Single Wall Oven

* IMPORTANT: Base has to be able to support the weight of the oven. Please check oven manual for minimum weight requirements.

minimum 1/2" (13 mm) required between cut-outs*

Warming Drawer

** For WD30W, the installed dimension may differ. This drawing based on a 3/4" (19 mm) thick custom panel.

measurements in inches (mm)

Standard installation
30" speed oven or microwave above a single oven***

28 1/2" (724 mm)

19 1/4" (488 mm)

23 1/2" (597 mm)

27-28 5/8" (686-727 mm)

min. 4 3/4" max. 18" (121-456 mm)

Measurements in inches (mm)

* Junction box may be located above or next to the unit within the reach of the power cable.

** Junction box may be located below (depending on space) or next to the unit within the reach of the power cable.

*** Most combinations available as combo oven (one cut-out, one electrical hook-up).

Minimum dimension between cut-out:

- 1" (25 mm) for wall oven cut-out height of 28 5/8" (727 mm)
- 2 5/8" (67 mm) for wall oven cut-out height of 27" (686 mm)

Flush installation
Speed oven or microwave above a 30" single oven**

Cleats

1" (25 mm)

20 1/8" (511 mm) flush cutout height

29 1/8" (740 mm) flush cutout height

**24 1/2" (622 mm)

*** Flush installation requires a base plate underneath the body: 30" products—Dimensions: H 5/16" (8 mm) x W 28 1/2" (724 mm) x D 22 1/2" (571 mm)

minimum 1/2" (13 mm) required between cut-outs*

* IMPORTANT: Base has to be able to support the weight of the oven. Please check oven manual for minimum weight requirements.

** Most combinations available as combo oven (one cut-out, one electrical hook-up).

measurements in inches (mm)

These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.