

Hood



Scan code to find out more





90cm ceiling mounted hood
LR97CAQ50B

Design	<ul style="list-style-type: none"> LED display Radio remote control 	<ul style="list-style-type: none"> LED light Dimmer light with soft light function
Features	<ul style="list-style-type: none"> Exhaust or re-circulate air operation 3 speed levels 2 intensive setting Intensive setting with automatic reset facility 	<ul style="list-style-type: none"> 10 minutes run-on program Saturation indicator for metal filter Rim ventilation
Technical Information	<ul style="list-style-type: none"> Extraction capacity 798m³/h (EN 61591) Total connected load 174W (13A plug) Tube connection diameter 150mm 	
Appliance Dimensions (H x W x D)	299 x 900 x 500mm	
Cut out Dimensions (Exhaust operation) (H x W x D)	299 x 888 x 487mm	
Supplied Accessory	2 dishwasher-safe brushed steel filters	
Optional Accessories	<ul style="list-style-type: none"> cleanAir Recirculation kit (LZ20JCD50) cleanAir Regenerative Charcoal Filter for LZ20JCD50 (LZ00XXP00)* <p>* Maximum 10 years lifespan: the regenerative filter can be generated up to 30 times, regeneration should be carried out in an oven at 200°C for 2 hours every 4 months with normal daily use of approximately 1 hour.</p>	
Country of Origin	Germany	
Expert Services	<ul style="list-style-type: none"> Product consultation with unlimited product hotline inquiry Kitchen planning consultation with pre-installation site measurement Professional installation 	
Recommended Retail Price	HK\$26,800	


Home Connect function is currently unavailable in Hong Kong and Macau region.

The fan outlet can be turned in all four directions




Never fit directly onto plasterboard or similar lightweight construction materials of the suspended ceiling. A suitable substructure is required that is securely fixed to the concrete ceiling.

Exhaust operation




A: Optimal Performance 700-1500
* from upper edge of pan support (gas hob)

Re-circulate air operation





A: Optimal Performance 700-1500
B: From upper edge of pan support
C: The distance can be reduced by up to 70mm provided that the height of the suspended ceiling is min. 340mm



A: Optimal Performance 700-1500
* from upper edge of pan support (gas hob)

Installation with cleanAir Recirculation Kit



Measurements in mm

BSH Home Appliances Limited

BSH Home Appliances Group is a Trademark Licensee of Siemens AG

Customer Contact Hotline: 2565 6151 (Hong Kong) / 0800 030 (Macau local call only)

Website: www.siemens-home.bsh-group.com.hk

• Specification and technical information subject to change.

• Right of technical modification reserved, colours may vary slightly from illustrations.

© 2021 by BSH Home Appliances Limited. Reproduction, complete or in part, only with the express permission of BSH.