GAGGENAU



Combi-microwave oven
Gaggenau Expressive series
GM 480/GM 481

Right-hinged

GM 480 720
Stainless steel behind smoked glass.
Width 30″ (76 cm).

Left-hinged

GM 481 720
Stainless steel behind smoked glass.
Width 30″ (76 cm).

Included accessories

1 wire rack.
1 door opening aid.
1 glass tray.

Installation accessories

GA 301 010
Gaggenau adjustable shelf.
Installation kit for 30″ (76 cm) appliances. For use in vertical installations where a perfect 3/16″ (5 mm) gap between Gaggenau Expressive Series appliances, and a single cut out are desired. Can support GS Combi-steam oven or GM Combi-microwave oven. Note this is not required as standard cabinet shelves can be used.
Includes mounting brackets, cover and screws.
Please note the following two exceptions for the use of the Gaggenau adjustable shelf:
— Exception One: When stacking a GO oven on top of another GO oven, a standard cabinet shelf (wood) is required.
— Exception Two: When stacking a GC coffee machine above a GM Combi-microwave oven, a standard cabinet shelf (wood) is required.

Optional accessories

BA 010 051
Core temperature probe.
Compatible with GO, GS, GM.

BA 036 166
Wire rack, chromium-plated.
Without opening, with feet.

BA 046 118
Glass tray.
1″ deep (24 mm).

Part No. 10044742
Door opening aid door accessory.

Highlights

— Handleless full glass door with electronic door opening.
— Full touch display with stainless steel control ring.
— Light and display response upon user detection.
— Single operation and combination of microwave and oven.
— Automatic programs and setting recommendations.
— Oven cavity size 2.1 cu. ft. (60 liters).
— Sabbath mode certified by Star-K.

Heating methods / Programs

Microwave operation with 6 output levels: Max (1,000), 600, 450, 360, 180, 90 W.
Oven operation with 9 heating methods:
— Convection from 184 °F to 445 °F.
— Broil + circulated air from 86 °F to 445 °F.
— Warm beverages, Max mircowave level.
— Reheat from 360 W to 600 W.
— Drying from 86 °F to 176 °F.
— Low temperature from 86 °F to 194 °F + microwave.
— Dough proofing from 86 °F to 122 °F.
— Keep warm, with special microwave level.
— Defrost from 90 W to 360 W.
Convection and Broil + circulated air freely combinable with microwave output levels 450, 360, 180 and 90 W.
70 programs
(automatic programs and setting recommendations).
Option to save up to 30 favorites.

Operation

Soft-close side-opening door with 110° opening angle.
Electronic door opening.
Full touch display with control ring.
42 display languages available.
User detection, adjustable distance.
Information key with use indicators.
Animated quick guides to assist appliance operation.

Features

Innowave (inverter technology) for uniform microwave output.
Precise temperature control with display of the current temperature.
Broil can be added briefly in convection mode for additional browning.
Connection for core temperature probe (oven temperature probe usable).
Programmable automatic door opening at cooking time end to avoid overcooking.
Timer functions: cooking time, cooking time end, count-up timer.
Long-term timer (Sabbath mode, Star-K certified).
Convection fan rotates in both directions for ideal heat distribution.
Optimum visibility of the food thanks to side lighting.
2 rack levels and option of placing the food in suitable accessories directly on the cooking compartment floor.

Selected digital services (Gaggenau Home Connect®)

Remote control and monitoring.
Cooking time estimation when using the core temperature probe.
Door opening via voice assistant.

Please read additional information on Gaggenau Home Connect® on page 271.

Safety

Child lock to prevent accidental switch on or operation of the appliance.
Electronic door lock to prevent unintentional opening of the appliance door.
Safety shut-off.
Thermally insulated door with triple glazing.
Cooled housing with temperature protection.

Cleaning

Hygienic stainless steel interior with heat resistant glass base.
Cleaning aid program.


Planning notes

Plan the cutout without back wall.
Door hinge not reversible.
Protrusion from appliance front to cabinet 1 5/8″ (42 mm).
Consider the overhang when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the side-opening door and the minimum required distance to the wall.
Door opening angle appr. 110° (delivery status) can be reduced to appr. 97° if required.
The door opening aid accessory should be attached before Shabbos, as it may not be permanently attached on Shabbos.

The electrical box must be accessible and located outside the built-in cutout. To comply with UL/CSA norm, the upper edge of the Combi-microwave front must be at a minimum height of ≥ 31″ (787 mm).

Rating

Total rating: 2,300 W (208 V); 2,900 W (240 V).
Total amps: 12.1 A.
Minimum fuse protection: 20 A, double-pole breaker.
120/208 - 240 V, 60 Hz, 4-wire.
Plan for a 59″ connecting cable (hardwire required).
Gaggenau Home Connect® functionality via WiFi.



A: Accessible electrical connection
B: Fixed cable
* The width tolerance as shown in the drawing indicated by the + 5/16″ (+8 mm) is the adjustment possible within the cabinet. Adjustments can be made between 5/8″ – 13/16″ (16-20 mm) for installation using the "centering parts" within the cabinet for perfect alignment. See installation instructions for details.

Numbers indicated inside parenthesis ( ) = mm

www.gaggenau.com/us
Revised: September 2026

PFAS

Gaggenau reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cut out. Warranties: Please see Use & Care manual or Gaggenau website for statement of limited product warranty. For more information on our entire line of products, go to www.gaggenau.com or call 1-877-442-4436.