



Register your new Bosch now: http://www.bosch-home.co.uk



Sensixx **DS38** i-Temp / Hygiene



en Operating instructions

Index	pag	
General safety instructions	4	
Description		
1. Preparations	7	
2. Programme selection	8	
3. Special programs	9	
3.1 "i-Temp Advanced" programme	9	
3.2 "AntiShine" programme	9	
3.3 "Hygiene" programme	9	
3.4 "Calc'nClean" programme	10	
4. "PulseSteam" function	10	
5. "Intelligent steam" function	10	
6. Ironing without steam	10	
7. Vertical steam	10	
8. Energy saving "eco" button	11	
9. Auto shut-off	11	
10. Fabric protection soleplate cover	11	
11. Calc'nClean Perfect	12	
11.1 Cleaning the Boiler	12	
11.2. Rinsing the iron steam chamber	13	
12. Cleaning & Maintenance	15	
13. Storing the appliance	16	
Tips to help you save energy		
Trouble shooting		
Guarantee conditions		

BOSCH 3

EN • Operating instructions

Thank you for buying the Sensixx DS38 steam station, the new steam-ironing system from Bosch.

Carefully read through the operating instructions for the appliance and safeguard them for future reference.

You can download this manual from the local homepages of Bosch.

General safety instructions

Э
t
n ot
S
ל ב

- This appliance has been designed exclusively for domestic use and must not be used for industrial purposes.
- This appliance must be used only for the purposes for which it was designed, i.e. as an iron. Any other use will be considered improper and consequently dangerous. The manufacturer will not be held responsible for any damage arising from misuse or improper use.
- This appliance is to be connected and used in accordance with the information stated on its characteristics plate.
- This appliance must be connected to an earthed socket. If it is absolutely necessary to use an extension cable, make sure that it is suitable for 16A and has a socket with an earth connection.
- If the safety fuse fitted in the appliance blows, the appliance will be rendered inoperative. To restore normal operation the appliance will have to be taken to an authorised Technical Service Centre.
- In order to avoid that, under unfavourable mains conditions, phenomena like transient voltage drops or lighting fluctuations can happen, it is recommended that the iron is connected to a power supply system with a maximum impedance of 0.37 Ω.
 If necessary, the user can ask the public power supply company for the system impedance at the interface point.
- The appliance must never be placed directly under the tap to fill the water tank.
- Unplug the appliance from the mains supply after each use, or if a fault is suspected.
- The electrical plug must not be removed from the socket by pulling the cable.
- Never immerse the iron in water or any other fluid.
- Do not leave the appliance exposed to weather conditions (rain, sun, frost, etc.)

Important:

- This appliance reaches high temperatures and produces steam during use, this could cause scalds or burns if not used properly.
- The steam hose, base station, metal plate at the bottom of the removable iron pad (2) and in particular the iron can get hot when used. This is normal.
- Never aim the steam at people or animals.
- Do not allow the power cable to come into contact with the soleplate when it is hot.
- Be aware that the system can keep on steaming for a short additional time after releasing the steam trigger. This is a normal function.

Advice on disposal


Our goods come in optimised packaging. This basically consists in using non-contaminating materials which should be handed over to the local waste disposal service as secondary raw materials. Your local town council can give you information about how to dispose of obsolete appliances.





This appliance is labelled in accordance with European Directive 2012/19/EU concerning used electrical and electronic appliances (waste electrical and electronic equipment - WEEE).

The guideline determines the framework for the return and recycling of used appliances as applicable throughout the EU.

■■ BOSCH







Description

- 1.Water tank
- 2. Removable iron pad
- 3. Iron lock system "SecureLock"
- 4."Calc" automatic clean warning indicator light
- 5. "Water tank empty" indicator light
- 6.Energy saving "eco" button and indicator light (green)
- 7. Ironing programme indicator lights
- 8. "Calc'nClean" decalcification programme and indicator light
- 9. Programme selector and illuminated ring.
- 10."on-off" power button.
- 11. Steam hose
- 12. "Calc'nClean Perfect" scale collector*
- 13. Mains cable with storage facility
- 14.Steam release button
- 15.Steam shot button "PulseSteam"*
- 16.Iron pilot light
- 17.Soleplate
- 18. Fabric-protection soleplate cover*

1. Preparations

 Release the iron from its lock system (3) by pulling the lever located at the heel of the iron backwards.



2. Remove any label or protective covering from the soleplate (17).

- 3. Place the appliance horizontally on a solid, stable surface. You may remove the iron pad from the appliance (2) and place the iron on it on another solid, stable, horizontal surface.
- 4. Fill the water tank, making sure not to pass the "max" level mark.





- 5. Unwind the mains cable (13) fully and plug it into an earthed socket.
- 6. Set the power button (10) to the on position.
- 7. The appliance will shift automatically to the "i-Temp Advanced" programme (see section 3.1). The corresponding indicator light (7) will flash, and after a few minutes, will remain lit continuously. Two beeps will be heard indicating that the appliance is ready to use.



The steam generator will take more time to reach this state only upon the initial heating up, or after performing the descaling operation (Calc'nClean). When water is already present in the steam generator during regular use, heat up time to reach the operating temperature will be faster.

8. This appliance has a built-in water level sensor. The "Water tank empty" indicator light (5) will light and three beeps will be heard when the water tank has to be filled.

Attention! If the water tank is empty when one of the ironing programs is selected, the indicator light (7) corresponding to such programme will flash until the water tank is filled.



Important:

- Normal tap water can be used. To prolong the optimum steam function, mix tap water with distilled water 1:1. If the tap water in your area is very hard, mix tap water with distilled water 1:2.
- You can inquire about the water hardness with your local water supplier.
- The water tank can be filled at any time while using the appliance.
- To avoid damage and/or contamination of the water tank and the boiler, do not put perfume, vinegar, starch, descaling agents, additives or any other type of chemical product into the water tank.

Any damage caused by the use of the aforementioned products, will make the guarantee void.

- The iron is not designed to rest on its heel. Please always position it horizontally on the iron pad (2).
- The iron pad can be placed into the specially designed recess on the appliance or somewhere suitable alongside the ironing area.

Never rest the iron on the appliance without the iron pad!

- During its first use the iron may produce certain vapours and odours, along with white particles on the soleplate (17), this is normal and it will stop after a few minutes.
- While the steam release button is pressed, the water tank may produce a pumping sound, this is normal, indicating that water is being pumped to the steam tank.



2. Programme selection

Your steam station has a programme selector (9) for choosing the different ironing programs.



Each programme automatically sets an appropriate combination of temperature and steam which is suitable for the kind of garment selected.

By turning the programme selector you can choose the kind of garment and fabric to be ironed. The corresponding indicator light (7) will flash until the temperature and steam level suitable for the programme selected are reached.

From this moment on, the indicator light will remain lit continuously and two beeps will be heard indicating that the appliance is ready to use.

If the garment to be ironed does not correspond to any of the programs supplied, check the temperature instructions shown on the care label of the garment.

Temperature	Programme
•	Synthetics
••	Wool**
•••	Cotton / Jeans
max	Linen

Tips:

- Sort your garments out based on their cleaning symbol labels, always starting with clothes that have to be ironed at the lowest temperatures.
- For mixed fabrics, select the temperature corresponding to the most delicate fabric.
- If you are not sure what the garment is made of then begin ironing at a low temperature and decide on the correct

temperature by ironing a small section not usually seen when worn

- At the beginning of each use, it is possible that drops of water will be dispensed alongside steam.
 Therefore, it is advisable to try the iron on the ironing board or a piece of cloth to start with.
- For better ironing results, iron the last strokes without steam to dry the garment.
- ** The wool cycle of this iron has been approved by The Woolmark Company for the ironing of pure wool products provided that the products are ironed according to the instructions on the garment label and those issued by the manufacturer of this iron. R1502. In UK, Eire, Hong Kong and India the Woolmark trade mark is a certification trade mark.



3. Special programs



3.1 "i-Temp Advanced" programme

i-Temp Advanced

This steam station has an "i-Temp Advanced" programme. If this programme is selected, an appropriate combination of temperature and steam is set, which is suitable for all fabrics that can be ironed. The "i-Temp Advanced" programme prevents clothes from being damaged due to an unsuitable temperature being selected. The "i-Temp Advanced" programme does not apply to fabrics that cannot be ironed. Please check the garment care label for

details or try ironing on a part of the cloth



3.2 "AntiShine" programme*



This steam station has an "AntiShine" programme. If this programme is selected and the steam release button (14 or 15*) is regularly pressed, the risk of shiny marks on the garment due to the ironing is reduced.



3.3 "Hygiene" programme*

This steam station is equipped with a special "Hygiene" programme.

The innovative hygienic steam technology removes 99.9% of microbes. Suitable for all kinds of fabrics and extremely efficient in both thick and delicate garments. The unique combination of temperature and interval steam provides a sanitizing effect requiring no chemical additives.

Please proceed as follows:

1. Choose the "Hygiene" programme by turning the selector (9).



- 2. Place the iron on the garment or fabric you want to disinfect.
- Press continuously the steam release button (14) on the bottom of the handle to release powerful shots of hygienic steam. Slowly iron the whole garment to enhance the final result.

not visible normally.

Notes:

- To ensure the high efficiency of the Hygiene programme, the system has to be reset after 20 minutes. "Hygiene" indicator lamp blinks five times and the steam generator switches automatically to the "i-Temp Advanced" programme.
- If desired to continue in the "Hygiene" programme, please wait till the Program-LED of the "i-Temp Advanced" programme stops blinking followed by two beeps. After that, you can choose again the "Hygiene"-programme by turning the selector (9).
- Energy saving setting ② cannot be activated while the "Hygiene" programme is selected.

When the steam release button is activated, the steam generator will release three powerful shots of steam so that the steam reaches even deeper into the fabrics. Briefly press the steam shot button (15*) on the top of the handle.

Remarks:

- It is possible to stop the shots of steam by quickly pressing the steam button again.
- Some water drops may appear when you use the "PulseSteam" function for the first time.

The water drops will disappear after you have used the function for some time.

3.4 "Calc'nClean" programme

See section 11.



5. "Intelligent steam" function

This system has intelligent steam control, which, after releasing the steam release button (14 or 15*), provides a small amount of additional steam.

The additional steam can always be stopped by briefly pressing the steam release button once again.



6. Ironing without steam

Begin ironing but without pressing the steam release button (14 or 15*).



4. "PulseSteam" function



This appliance has a special function for tackling difficult creases.




7. Vertical steam


This can be used to remove creases from hanging clothes, curtains etc. Warning!:



Never direct the steam jet at garments that are being worn. Never aim the steam at people or animals. 1. Select "Jeans / • • •" programme to get the optimal steam amount.



- 2. Hold the iron in an upright position 15 cm away from the garment being steamed.
- You can steam iron curtains and hanging garments (jackets, suits, coats...) by placing the iron in a vertical position and pressing the steam release button (14 or 15*).



е

8. Energy saving "eco" button

Push the energy saving button **(3)** (6). If the energy saving setting is selected, you can save up to 30% of the energy and 40% of the water consumption (*), and still achieve good results when ironing most of your garments.

It is advisable to use the normal energy setting only for thick and very wrinkled fabrics.

(*) In comparison to the maximum setting.



9. Auto shut-off

If during ironing, the steam release button (14 or 15*) on the iron handle is not pressed for a certain length of time (8 minutes), the steam station will automatically switch off. The illuminated ring around the programme selector (9) will flash when auto shut-off has been activated. Three beeps will be heard

To switch the steam station back on, press the steam release button again.




at the same time.

10. Fabric protection soleplate cover

The fabric-protection soleplate cover (18*) is used for steam-ironing delicate garments at maximum temperature without damaging them. Use of the soleplate cover also does away with the need for a cloth to prevent shine on dark materials.

It is advisable to first iron a small section on the inside of the garment to see if it is suitable.




To attach the soleplate cover to the iron, place the tip of the iron into the end of the soleplate cover and pull the elastic strap over the lower rear of the iron until it fits tightly. To release the soleplate cover, pull the elastic strap and remove the iron.

The fabric-protection soleplate cover may be purchased from our customer service or from our website.

Accessory code (After-sales)	Name of accessory (online shop)
00571510	TDZ2045

2 Unscrew the scale collector (12*) and take it out.





11. Calc'nClean Perfect

Automatic clean warning

The "Calc" automatic clean warning indicator light (4) will flash indicating that boiler and iron steam chamber must be rinsed.

Leave the appliance unplugged for more than two hours, check carefully that the appliance is cold and that the water tank (1) is empty.

Please proceed as follows:



11.1 Cleaning the Boiler

Do not use descaling agents for rinsing out the boiler, as they could damage it.


Fix the iron to the stand by inserting the tip of the iron into the front slot and moving the lock system (3) against the heel of the iron. Place your appliance on the edge of your kitchen sink.



To wash the scale collector, place it under the water tap and wash it up until calc residues are removed. Squeeze it as indicated in the picture a).

To obtain the best result, you may immerse the scale collector for approximately 30 minutes in tap water (250 ml) mixed with a measure (25 ml) of descaling fluid, as indicated in the picture b).

Then, rinse it again with water (very important!).



The descaling fluid can be obtained from our Aftersales Service or Specialist outlets:


Accessory code	Name of accessory
(After-sales)	(Specialist outlets)
00311715	TDZ1101

4 Holding your steam generator in upside down position, and using a jug, fill the boiler (in the base unit) with 1/4 litre of water.




Shake the base unit for a few moments and then empty it completely over a sink or bucket. To obtain the best result, we recommend that this operation is performed twice.

Important: before re-closing, make sure no water remains in the boiler.



6 Replace and tighten up the scale collector.






11.2. Rinsing the iron steam chamber

Fill the tank with tap water.



2 Plug in the mains cable and set the power button (10) to the "I" position.




3 By turning the programme selector (9), choose "Calc'nClean" decalcification programme. The indicator light (7) will start flashing.




Wait until the indicator light (8) stops flashing and remains lit continuously. Two beeps will be heard at the same time.



5 Hold the iron over the sink or a container to collect the water.




Press the steam release button (14) and gently shake the iron. Boiling water and steam will be released, carrying scale and/or deposits that might be inside. After approximately one minute, the "Calc" automatic clean warning indicator light (4) will go off. Keep on shaking the iron gently for five minutes while the steam release button is pressed, so that water and steam clean the chamber completely.




Without pressing the steam release button (14), turn the programme selector (9) and choose "Linen / max" programme. The water in the steam chamber will start evaporating.



Wait until all the water inside the chamber has been evaporated. Then, you can set the power button (10) to the "O" position.




To clean the soleplate, immediately rub off any residue by running the hot iron over a wet cotton cloth.




3. If the soleplate is soiled with dirt or scale, clean it with a damp cotton cloth.



4. If the cloth is synthetic, it may melt due to the high temperature on the soleplate. Switch off the steam and rub off any residue immediately with a thickly folded, damp cotton cloth.




5. Never use abrasive products or solvents. To keep the soleplate smooth, you should avoid hard contact with metal objects. Never use a scouring pad, or chemicals to clean the soleplate.



3

12. Cleaning & Maintenance



 After ironing, pull out the plug and allow the appliance to cool down before cleaning.




2. Wipe the housing, handle and iron body with a damp cotton cloth.



13. Storing the appliance

1. Set the power button to the "O" position and disconnect the mains cable.




2. Always allow the appliance to cool down before storing it.



3. Place the iron on the iron pad (2), standing on the soleplate, and fix it by inserting the tip of the iron into the front slot and moving the lock system (3) against the heel of the iron.



4. Empty the water tank, store the mains cable on the cord storage facility and the steam hose in the storage fixing. Do not wrap the cords too tight.



5. Hold the iron's handle when moving the appliance.





Tips to help you save energy

Steam production consumes the most energy. To help minimise the energy used, follow the advice below:

- Start by ironing the fabrics that require the lowest ironing temperature. Check the recommended ironing temperature on the label on the garment.
- Try to iron the fabrics while they are still damp and reduce the steam setting.
 Steam will be generated from the fabrics rather than the iron.
- If you tumble dry your fabrics before ironing them, set the tumble drier on the 'iron dry' programme.



`\overline{Control of the control of

- File		
Problem	Possible causes	Solution
The "Calc" indicator light (4) flashes.	Boiler and iron must be rinsed.	Rinse the boiler and the iron according to the cleaning instructions in this manual.
The ironing programme indicator light (7) flashes continuously.	1. The water tank (1) is empty.	1. Fill the water tank.
The steam generator does not come on.	 There is a connection problem. The power button is not switched on. 	 Check the mains cable (13), the plug and the socket. Set the power button (10) to the "I" position.
The iron does not heat up.	1. The power button is not switched on. 2. The temperature is set to a low position.	Set the power button (10) to the "I" position. Set the temperature to the desired position.
The iron begins to smoke when switched on.	During first use: certain components on the appliance have been lightly greased at the factory and may produce a little smoke when initially heated. During subsequent use: the soleplate may be soiled.	This is completely normal and will stop after a short while. Clean the soleplate according to the cleaning instructions in this manual.
Water flows through the holes on the soleplate.	The water is condensing inside the pipes because steam is being used for the first time or has not been used for a long time.	Point the iron away from the ironing area and press the steam release button until steam is produced.
Dirt comes out through the soleplate.	There is a build up of scale or minerals in the boiler and iron. Chemical products or additives have been used.	1. Carry out a cleaning cycle (see "Calc'nClean Perfect" section). 2. Never add products to the water. Use tap water mixed 50% with distilled or demineralised water. To prolong the optimum steam function, mix tap water with distilled water 1:1. If the tap water in your area is very hard, mix tap water with distilled water 1:2. Clean the soleplate with a damp cloth.
The iron does not produce any steam.	The boiler is not switched on or the water tank is empty. The water tank is not fitted onto the housing correctly.	Set the power button (10) to the "I" position, and/or fill the water tank. Fit the water tank back onto the housing correctly.
The ironed garment turns dark and/or sticks to the soleplate.	The selected temperature is too high and has damaged the garment.	Select a suitable temperature for the material being ironed and clean the soleplate with a damp cloth.

Problem	Possible causes	Solution
The soleplate turns brown.	This is a regular consequence of continued use over a long period of time.	Clean the soleplate with a damp cloth.
The appliance makes a pumping sound.	 Water is being pumped into the steam tank. The water tank is not fitted onto the housing correctly. The sound will not stop. 	 This is normal. Fit the water tank back onto the housing correctly. If the sound will not stop, do not use the steam generator and contact an authorised technical service centre.
Loss of pressure during ironing.	Steam release button has been activated for too long a period of time, that is, it has been pressed too frequently.	Use the steam release button at intervals. This improves the ironing result as the textiles will be steamed, dried and ironed properly.
Water spots appear on the garment during ironing.	May be caused by steam condensed on the ironing board.	Wipe the textile cover of the ironing board, and iron any water drops to dry them.
Water spots appear on the garment during use of the "PulseSteam" function.	Water spots are caused by steam condensation in the hose when cooling down after use.	Water drops stop coming out of the soleplate after using the "PulseSteam" function for some time.
The hose gets hot during use.	This is normal. It is caused by the steam passing through the hose during steam ironing.	Place the hose on the opposite side so that you cannot touch the hose during ironing.
Water leakage from the boiler.	Scale collector (12*) located at the bottom of the appliance is loose.	Tighten up the scale collector.
The iron does not stop steaming after placing it on the pad (2).	"PulseSteam" function has been activated.	Just press the trigger once again and the iron will stop steaming at once.

If the above does not solve the problem, get in touch with our customer service.

Guarantee conditions

The terms of the guarantee for this appliance are in accordance with that stated by our representative for the country in which it is sold.

The details of these conditions can be obtained from the retailer from whom the appliance was purchased. The purchase receipt must be presented when making any claims against the terms of this guarantee.

Customer Service Great Britain

Bosch Customer Service Grand Union House Old Wolverton Road Milton Keynes MK12 5PT

UK +44 (0)344 892 8979 IRL +353 (0)1450 2655 www.bosch-home.co.uk