en Before using for the first time, read the instruction manual and the safety information it contains. **Programmes** Setting up Home Connect Overview of water hardness settings Setting the water softening sys-Dishwasher tem You can find an overview of the Medium 1.5 - 1.8 H02 The programme data has been meas-Tip: Connect your appliance to a mobile device. You can conured in the laboratory according to water hardness values that can veniently change all settings using the Home Connect app. Medium 1.9-2.1 H03 **1.** Press (¹). European standard EN 60436. be selected here. 2.2 - 2.9 H04 2. To open the basic settings, press Medium 1. Install the Home Connect app on your mo-GET IT ON A table of country-specific units Setup 3 sec. for 3 seconds. The consumption figures depend on 3.0 - 3.7 H05 Google Play Hard bile device and follow the instructions. can be found in the instruction the programme and additional func- The display shows Hxx. Hard 3.8 - 5.4 H06 tion selected. manual. The display shows set. H07 Hard 5.5 - 8.9 pp Store The runtime will change if the rinse 3. Press Start repeatedly until the right Hardness mmol/l Setting aid system is switched off or rinse aid water hardness has been set. 2. Scan the QR code with the Home Connect value range needs to be added. 4. To save the settings, press app. Soft H00 0 - 1.1 Setup 3 sec. for 3 seconds. guide Programme 1) Duration [h:min] Soft 1.2 - 1.4 H01 2) Energy [kWh] 3) Water [I] 1) 2:10 - 2:15 Intensive 2) 1.300 - 1.350 Intensive 70° 3) 11,0 - 13,5 Quick reference 1) 1:45 - 2:45 Auto 2) 0.850 - 1.350 S Adding special salt Ξ Auto 45-65° 3) 9,5 - 15,5 1) 4:30 To avoid damage to the appliance, only add special 3. Add the special salt to the Eco 2) 0.923 salt to the dispenser for special salt just before the dispenser. The water in the Eco 50° 3) 10.5 programme starts. dispenser is displaced and 1) 1:00 1. Unscrew the lid of the dispenser for special salt forced out. Never add de-Express 2) 1.100 and remove. tergent. Express 65° - 1h 3) 10.0 2. On initial start-up: Fill the dispenser right up with 1) 2:10 Machine water. 4. Place the lid back on the dispenser and turn to Care 2) 1,450 close. Machine Care 3) 15,0 1) 0:15 - 0:15 ☆ 2) 0,050 - 0,050 * Adding rinse aid *Favourite 3) 4,0 - 4,0 1. Press the catch on the lid 2. Add rinse aid up to the of the dispenser for rinse max mark. aid 1 and lift 2. 3. Close the lid of the dispenser for rinse aid. The lid clicks into position. ð Adding detergent $/\!\!/$ 1. Add the detergent to the 2. Close the lid of the deter-50 m CLICK dry detergent dispenser. 25 m gent dispenser. The lid clicks into position.

How to use your appliance

SMS2ITW41G

(020402)

9001627163

- 1. Load the tableware.
- Only clean tableware that is suitable for dishwashers. Remove large remnants of food from the tableware. Check that the sprav arms can ro-
- tate freely.
- 2. Add detergent.
- 3. Switch on the appliance O.

- 4. Select the programme.
- 5. Start the programme Start.
- 6. Remove the tableware at the end of the programme.
- 7. To cancel the programme, press Reset 4 sec. for approx. 4 seconds. The programme is cancelled and ends after approx. 1 minute.


Cleaning filters

- 1. After each wash check the filters for residue.
- 2. Turn the coarse filter anticlockwise 1 and remove the filter system 2.
- 3. Pull down the micro filter to remove.

()



- 5. Clean the filter elements under running water.
- 6. Re-assemble the filter system.
- and turn the coarse filter clockwise. Make sure that the arrow markings match up.




4. Insert the lower spray arm. The spray arm clicks into position.

- **1.** Unscrew the upper spray arm 1 and pull down to remove 2.
- 2. Pull up the lower spray arm to remove.

3. Check the outlet nozzles on the spray arms for blockages un-

der running water and remove any foreign bodies.

5. Insert the upper spray arm and screw it firmly in place.



Clean wastewater pump

- 1. Disconnect the appliance from the power supply.
- 2. Remove the filter system.
- **3.** Scoop out any water.
- **4.** Prise off the pump cover using a spoon and grip it by the crosspiece.



- 5. Lift the pump cover inwards at an angle and remove.
- 6. Remove any remnants of food and foreign bodies in the area of the impeller.
- 7. Insert the pump cover 1 and press down 2.
- The pump cover clicks into position.



8. Install the filter system.

Troubleshooting

Fault	Cause and troubleshooting	Fault	Cause and troubleshooting	Fault	Cause and troubleshooting
E:32-00 will light up al- ternately or indicator for water supply lights up.	Supply hose is kinked. Install the supply hose without kinks. 	E:92-40 will light up al- ternately.	Filters are soiled or blocked. • Clean the filters.	Removable streaks are present on glasses, glass- ware with a metallic ap- pearance and cutlery.	Amount of rinse aid to be dispensed is set too high. Set the rinse aid system to a lower setting.
	Water tap is turned off. Turn on the water tap.	E:61-02 will light up al- ternately.	Wastewater pump is blocked. • Clean the wastewater pump.		No rinse aid has been added. Add rinse aid.
	Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 I/min when the water sup-		 Cover of the wastewater pump is loose Secure the cover of the Wastewater pump so it clicks into position. 	Rust spots on cutlery.	Cutlery is not sufficiently rust-resistant. Knife blades are often more severely affected. • Use rust-resistant tableware.
	ply is open. The filters in the water connection of the supply or AquaStop	Remnants of food on tableware.	 Tableware is placed too close together or basket is overfilled. Arrange tableware with sufficient space in between. The spray jets must reach the surfaces of the tableware. Avoid points of contact. 		Cutlery may also rust if washed together with rusting items. Do not wash rusting items.
	hose are blocked. 1. Switch off the appliance.			Detergent residue is present in the detergent dispenser or the tablet collecting tray. All LEDs light up or flash or the rinse programme does not continue run- ning.	 Spray arms were blocked by tableware so detergent was not rinsed out. Check that the spray arms are not blocked and can rotate freely. Electronics have detected a fault. Press the main switch button for approx. 4 seconds. The appliance is reset and restarted.
	 Pull out the mains plug. Turn off the water tap. Unscrew the water connection. 		 Spray arm rotation is blocked. Arrange tableware so that it does not obstruct spray arm rotation. 		
	5. Remove the filter from the supply hose		Spray arm nozzles are blocked. Clean the Spray arms.		
			Filters are soiled. ► Clean the filters.		
	6. Clean the filter.		Filters are inserted incorrectly and/or not engaged. 1. Insert the filters properly. 2. Engage the filters.		
	 Re-insert the filter in the supply hose. Screw the water connection back on. Check the water connection for leaks. 		Washing programme selected too weak.Select a more intensive washing programme.	_	
	10. Restore the power supply.11. Switch the appliance on.				

- **7.** Insert the filter system into the appliance