Setting up Home Connect

Tip: Connect your appliance to a mobile device. You can conveniently change all settings via the Home Connect app.

- 1. Install the Home Connect app on your mobile device and follow the instructions.
- 2. Scan the QR code using the Home Connect app.



Geogle Play

| Hardness | mmol/l | S | etting | |
|------------|----------|--------|---------|----|
| manual. | | | | |
| can be fo | und in t | he ins | tructio | 'n |
| A table of | country | y-spec | ific un | it |
| be selecte | ed here. | | | |
| water har | dness v | alues | that ca | а |

You can find an overview of the

Medium

Medium

Medium

Hard

Hard

Hard

1.5 - 1.8

1.9 - 2.1

2.2 - 2.9

3.0 - 3.7

3.8 - 5.4

5.5 - 8.9

H02

H03

H04

H05

H06

H07

| Hardness range | mmol/l | Setting value |
|-------------------|-----------|------------------|
| Soft | 0 - 1.1 | H00 |
| Soft | 1.2 - 1.4 | H01 |

Setting the water softening system

1. Press ⁽¹⁾.

- 2. To open the basic settings, press Setup 3 sec. for 3 seconds.
- ✓ The display shows Hxx.
- The display shows set.
- 3. Press Start repeatedly until the right water hardness has been set.
- 4. To save the settings, press Setup 3 sec. for 3 seconds.

The programme data has been measured in the laboratory according to European standard EN 60436. The consumption figures depend on the programme and additional func-

Programmes

tion selected. The running time will change if the rinse aid system is switched off or rinse aid needs to be added.

| Programme | 1) Duration [h:min] 2) Energy [kWh] 3) Water [l] | | |
|-------------------------|--|--|--|
| | 1) 2:05 - 2:15 | | |
| Intensive 70° | 2) 1,300 - 1,400 3) 11,5 - 14,0 | | |
| Auto Auto 45-65° | 1) 1:40 - 2:45 2) 0,900 - 1,500 3) 7,0 - 15,5 | | |
| Eco | 1) 4:35 2) 0.736 | | |
| Eco 50° | 3) 9,5 | | |
| R | 1) 4:00 | | |
| Silence 50 ¹ | 2) 1,050 3) 11,0 | | |
| (îh) | 1) 1:00 2) 1,300 | | |
| Express 65° - 1h | 3) 10,5 | | |
| | 1) 2:10 2) 1,350 | | |
| Machine Care | 3) 15,2 | | |
| | 1) 0:15 - 0:15 2) 0,050 - 0,050 | | |
| Favourite | 3) 4,0 - 4,0 | | |

takes longer, but is extremely quiet.

S Adding special salt Ξ To avoid damage to the appliance, only add special 3. Add the special salt to the salt to the dispenser for special salt just before the dispenser. The water in the programme starts. dispenser is displaced and 1. Unscrew the lid of the dispenser for special salt forced out. Never add deand remove. tergent. 2. On initial start-up: Fill the dispenser right up with water. 4. Place the lid back on the dispenser and turn to close. * Adding rinse aid *1. Press the catch on the lid 2. Add rinse aid up to the of the dispenser for rinse max mark. aid 1 and lift 2. max 3. Close the lid of the dispenser for rinse aid. The lid clicks into position. Adding detergent $/\!\!/$ 1. Add the detergent to the 2. Close the lid of the deter-50 m CLICK dry detergent dispenser. 25 m gent dispenser. The lid clicks into position.

How to use your appliance

1. Load the tableware.

Only clean tableware that is suitable for dishwashers. Remove large remnants of food from the tableware. Check that the spray arms can ro-

- tate freely.
- 2. Add detergent.
- 3. Switch on the appliance O.

- 4. Select the programme.
- 5. Start the programme Start.
- 6. Remove the tableware at the end of the programme.
- 7. To cancel the programme, press Reset 4 sec. for approx. 4 seconds. The programme is cancelled and ends after approx. 1 minute.

SMV4ECX14E

(010323)

9001633450

en

Cleaning filters

- 1. After each wash check the filters for residue.
- 2. Turn the coarse filter anticlockwise 1 and remove the filter system 2.



3. Pull down the micro filter to remove.





- 5. Clean the filter elements under running water.
- 6. Re-assemble the filter system.
- **7.** Insert the filter system into the appliance and turn the coarse filter clockwise. Make sure that the arrow markings match up.

| leaning | spray | arms |
|---------|-------|------|
| | | |


4. Insert the lower spray arm. The spray arm clicks into position.

- 1. Unscrew the upper spray arm ① and pull down to remove 2.
- 2. Pull up the lower spray arm to remove.

3. Check the outlet nozzles on the spray arms for blockages un-

der running water and remove any foreign bodies.

5. Insert the upper spray arm and screw it firmly in place.



Clean wastewater pump

- 1. Disconnect the appliance from the power supply.
- 2. Remove the filter system.
- **3.** Scoop out any water.
- **4.** Prise off the pump cover using a spoon and grip it by the crosspiece.



- 5. Lift the pump cover inwards at an angle and remove.
- 6. Remove any remnants of food and foreign bodies in the area of the impeller.
- 7. Insert the pump cover 1 and press down 2.
- The pump cover clicks into position.



8. Install the filter system.

Troubleshooting

| Fault | Cause and troubleshooting | Fault | Cause and troubleshooting | Fault | Cause and troubleshooting |
|--------------|---|--|---|--|---|
| ply is open. | | E:92-40 will light up al- ternately. E:61-02 will light up al- ternately. | Filters are soiled or blocked. ► Clean the filters. | Removable streaks are present on glasses, glass- ware with a metallic ap- pearance and cutlery. | Amount of rinse aid to be dispensed is set too high. Set the rinse aid system to a lower setting. |
| | | | Wastewater pump is blocked. Clean the wastewater pump. | | No rinse aid has been added. Add rinse aid. |
| | Turn on the water tap. The flow rate must be at least 10 I/min when the water sup- | | Cover of the wastewater pump is loose Secure the cover of the Wastewater pump so it clicks into position. | Rust spots on cutlery. | Cutlery is not sufficiently rust-resistant. Knife blades are often more severely affected. • Use rust-resistant tableware. |
| | The filters in the water connection of the supply or AquaStop | Remnants of food on tableware. | Tableware is placed too close together or basket is overfilled. Arrange tableware with sufficient space in between. The spray jets must reach the surfaces of the tableware. Avoid points of contact. | | Cutlery may also rust if washed together with rusting items. Do not wash rusting items. |
| | 1. Switch off the appliance. | | | Detergent residue is present in the detergent dispenser or the tablet collecting tray. | Spray arms were blocked by tableware so detergent was not rinsed out. Check that the spray arms are not blocked and can rotate freely. |
| | Turn off the water tap. Unscrew the water connection. | | Spray arm rotation is blocked. Arrange tableware so that it does not obstruct spray arm rotation. | | |
| | ply hose 6. Clean the filter. 7. Re-insert the filter in the supply hose. 8. Screw the water connection back on. 9. Check the water connection for leaks. | | Spray arm nozzles are blocked. ► Clean the Spray arms. | | |
| | | | Filters are soiled. ► Clean the filters. | | |
| | | | Filters are inserted incorrectly and/or not engaged. 1. Insert the filters properly. 2. Engage the filters. | | |
| | | | Washing programme selected too weak. ► Select a more intensive washing programme. | | |
| | | | | | |