Tip: Connect your appliance to a mobile device. You can conveniently change all settings via the Home Connect app.

- 1. Install the Home Connect app on your mobile device and follow the instructions.
- 2. Scan the QR code using the Home Connect app.



Get IT ON Google Play



Overview of water nargness settings				
You can find an overview of the	Medium	1.5 - 1.8	H:02	
water hardness values that can	Medium	1.9 - 2.1	H:03	
be selected here.	Medium	2.2 - 2.9	H:04	
A table of country-specific units can be found in the instruction	Hard	3.0 - 3.7	H:05	
manual.	Hard	3.8 - 5.4	H:06	
manual.	Hard	5.5 - 8.9	H:07	

Hard Setting value H:00 H:01

Setting the water softening system

1. Press ().

- 2. To open the basic settings, press Setup 3 sec. for 3 seconds.
- ✓ The display shows H:xx.
- The display shows set.
- 3. Press or + repeatedly until the right water hardness has been set.
- 4. To save the settings, press Setup 3 sec. for 3 seconds.

The programme data has been measured in the laboratory according to European standard EN 60436.

Programmes

tion selected. The running time will change if the

The consumption figures depend on the programme and additional funcrinse aid system is switched off or rinse aid needs to be added. Programme 1) Duration [h:min] 2) Energy [kWh] 3) Water [I] 1) 2:10 - 2:15 Ē 2) 1.300 - 1.350 Intensive 70° 3) 9,0 - 12,0 1) 1:45 - 2:45 Auto 2) 0,750 - 1,250 Auto 45-65° 3) 5,0 - 14,0 1) 4:35 Eco 2) 0.920 Eco 50° 3) 6.7 1) 4:05 P 2) 0.950 Silence 50 3) 6.7 1) 1:40 - 1:45 20 2) 0,700 - 0,750 Glass 40° 3) 10,0 - 13,5 1) 1:00 (1h) 2) 1,200 Speed 65° 3) 10,0 1) 0:35² (Trì 2) 0,700 Speed 45° 3) 10,0 E 1) 2:15 2) 1.350 Machine Care 3) 13.0 5 1) 0:15 - 0:15

2) 0,050 - 0,050 Favourite 3) 4,0 - 4,0 Suitable programme for running at night: it takes longer, but is extremely quiet. half standard load

Adding special salt \cong	
 To avoid damage to the appliance, only add special salt to the dispenser for special salt just before the programme starts. 1. Unscrew the lid of the dispenser for special salt and remove. 2. On initial start-up: Fill the dispenser right up with water. 	 Add the special salt to the dispenser. The water in the dispenser is displaced and forced out. Never add detergent. 4. Place the lid back on the dispenser and turn to close.
Adding rinse aid st	
 Press the catch on the lid of the dispenser for rinse aid ① and lift ②. 	 2 Add rinse aid up to the max mark. 3. Close the lid of the dispenser for rinse aid. The lid clicks into position.
Adding detergent ///	
1. Add the detergent to the dry detergent dispenser.	 2 Close the lid of the detergent dispenser. The lid clicks into position.
	To avoid damage to the appliance, only add special salt to the dispenser for special salt just before the programme starts. 1. Unscrew the lid of the dispenser for special salt and remove. 2. On initial start-up: Fill the dispenser right up with water. Adding rinse aid * 1. Press the catch on the lid of the dispenser for rinse aid ① and lift ②. Adding detergent // 1. Add the detergent to the dry detergent dispenser.

How to use your appliance

1. Load the tableware.

Only clean tableware that is suitable for dishwashers. Remove large remnants of food from the tableware. Check that the spray arms can ro-

- tate freely.
- 2. Add detergent.
- 3. Switch on the appliance O.

- 4. Select the programme.
- 5. Start the programme Start.
- 6. Remove the tableware at the end of the programme.
- 7. To cancel the programme, press Reset 4 sec. for approx. 4 seconds. The programme is cancelled and ends after ap-

prox. 1 minute.

SN25E102CZ


(010414)

9001643605

en

Cleaning filters

- 1. After each wash check the filters for residue.
- 2. Turn the coarse filter anticlockwise ① and remove the filter system ②.



3. Pull down the micro filter to remove.

)



- 5. Clean the filter elements under running water.
- $\textbf{6.} \ \text{Re-assemble the filter system}.$
- Insert the filter system into the appliance and turn the coarse filter clockwise. Make sure that the arrow markings match up.

leaning	spray	arms


4. Insert the lower spray arm.The spray arm clicks into position.

- **1.** Unscrew the upper spray arm ① and pull down to remove ②.
- 2. Pull up the lower spray arm to remove.

3. Check the outlet nozzles on the spray arms for blockages un-

der running water and remove any foreign bodies.

5. Insert the upper spray arm and screw it firmly in place.



Clean wastewater pump

- **1.** Disconnect the appliance from the power supply.
- 2. Remove the filter system.
- **3.** Scoop out any water.
- **4.** Prise off the pump cover using a spoon and grip it by the crosspiece.



- **5.** Lift the pump cover inwards at an angle and remove.
- **6.** Remove any remnants of food and foreign bodies in the area of the impeller.
- 7. Insert the pump cover ① and press down ②.
- The pump cover clicks into position.



8. Install the filter system.

Troubleshooting

Fault	Cause and troubleshooting	Fault	Cause and troubleshooting	Fault	Cause and troubleshooting
ply is open.	11.2	E:92-40 will light up al- ternately.	Filters are soiled or blocked.Clean the filters.	present on glasses, glass- ware with a metallic ap- pearance and cutlery. Rust spots on cutlery.	Amount of rinse aid to be dispensed is set too high. ► Set the rinse aid system to a lower setting.
		E:61-02 will light up al- ternately.	Wastewater pump is blocked. Clean the wastewater pump.		No rinse aid has been added. Add rinse aid.
	 Turn on the water tap. The flow rate must be at least 10 l/min when the water sup- 		Cover of the wastewater pump is loose ► Secure the cover of the Wastewater pump so it clicks into position.		Cutlery is not sufficiently rust-resistant. Knife blades are often more severely affected. Use rust-resistant tableware.
	The filters in the water connection of the supply or AquaStop hose are blocked. 1. Switch off the appliance.	Remnants of food on tableware.	Tableware is placed too close together or basket is overfilled. 1. Arrange tableware with sufficient space in between.		Cutlery may also rust if washed together with rusting items. Do not wash rusting items.
		The spray jets must reach the surfaces of the tableware. 2 Avoid points of contact.	Detergent residue is present in the detergent	Spray arms were blocked by tableware so detergent was not rinsed out.	
	 Turn off the water tap. Unscrew the water connection. 		 Spray arm rotation is blocked. Arrange tableware so that it does not obstruct spray arm rotation. 	dispenser or the tablet collecting tray.	 Check that the spray arms are not blocked and can rotate freely.
	 ply hose 6. Clean the filter. 7. Re-insert the filter in the supply hose. 8. Screw the water connection back on. 9. Check the water connection for leaks. 10. Restore the power supply. 		Spray arm nozzles are blocked. ► Clean the Spray arms.		
			Filters are soiled. ► Clean the filters.		
			Filters are inserted incorrectly and/or not engaged. 1. Insert the filters properly. 2. Engage the filters.		
			 Washing programme selected too weak. Select a more intensive washing programme. Adjust the sensitivity of the sensors. 		