en							
<u> </u>	Short and handy	Overview of water hardness settings			Setting water softening system	Programs	
e Dishwashe	everything your dishwasher needs. Before using for the first time, make sure you read both the op- erating and the installation instructions.	You can find an overview of the water hardness values that can be selected here. A table of country-specific units can be found in the instruction manual.Medium1.5-1.8 MediumMedium1.9-2.1 		 H02 H03 H04 H05 H06 H06 H07 Programme button A and press Start repeatedly until the display shows H:xx. Release programme button A and Start. Programme button A flashes. Press programme button C repeatedly until the right water hardness has been set. Press Start to save the setting. 		The program data has been measured in the laboratory according to European standard EN 60436.The consumption figures depend on the program and additional function selected.The runtime will change if the rinse aid system is switched off or rinse aid needs to be added.Program1) Duration [h:min]	
ice guide						ت / ت Intensive 70°	2) Energy [kWh] 3) Water [I] 1) 2:05 - 2:15 2) 1,400 - 1450 3) 12 - 15 1) 1:35 - 2:40 2) 0,950 - 1,550
en	S S	Adding special salt ${\mathfrak S}$				Auto 45-65°	3) 9 - 19
Quick reference		 To avoid damage to the appliance, only add special salt to the dispenser for special salt just before the programme starts. 1. Unscrew the lid of the dispenser for special salt and remove. 2. On initial start-up: Fill the dispenser right up with water. 		 Add the special salt to the dispenser. The water in the dispenser is displaced and forced out. Never add detergent. Place the lid back on the dispenser and turn to close. 		$\begin{array}{c c} & \overbrace{Eco}^{1} / \ eco & 1) 3:30 \\ & 2) 0,920 \\ & 3) 9,5 \\ \hline \\ $	2) 0,920 3) 9,5 1) 1:25 - 1:30 2) 0,850 - 0,900 3) 11 - 14 1) 1:00 2) 1,300 3) 10 1) 0:15
		Adding rinse aid *				PreRinse	3) 4
		 Press the catch on the lid of the dispenser for rinse aid ① and lift ②. 		max mark 3. Close the	e aid up to the k. e lid of the dispenser for rinse aid. icks into position.		
ТКЕ		Adding detergent ///					
(020403) SN536S01		1. Add the detergent to the dry detergent dispenser.	50 ml 25 ml 15 ml	gent dispe	lid of the deter- enser. cks into position.		
(020)	How to use your appliance						
01733616	 Load the tableware. Only clean tableware that is suitable for dishwashers. Remove large remnants of food from the tableware. Check that the spray arms can ro- Switch of the tableware tableware tableware. 		 Select the p Start the p Remove the gramme. 	programme S	tart. approx. 3	seconds. amme is cancelled	oress Reset 3 sec. for d and ends after ap-

9001733616 (020403) SN536S01KE

- 3. Switch on the appliance ①.

- 6. Remove the tableware at the end of the programme.
- The programme is cancelled and ends after approx. 1 minute.

Cleaning filters

- 1. After each wash check the filters for residue.
- 2 Turn the coarse filter anticlockwise ① and remove the filter system ②.




3. Pull down the micro filter to remove.

)



- 5. Clean the filter elements under running water.
- 6. Re-assemble the filter system.
- Insert the filter system into the appliance and turn the coarse filter clockwise. Make sure that the arrow markings match up.



4. Insert the lower spray arm.The spray arm clicks into position.

- **1.** Unscrew the upper spray arm ① and pull down to remove ②.
- 2. Pull up the lower spray arm to remove.

3. Check the outlet nozzles on the spray arms for blockages un-

der running water and remove any foreign bodies.

5. Insert the upper spray arm and screw it firmly in place.



Clean wastewater pump

- **1.** Disconnect the appliance from the power supply.
- **2.** Remove the filter system.
- 3. Scoop out any water.
- **4.** Prise off the pump cover using a spoon and grip it by the crosspiece.



- **5.** Lift the pump cover inwards at an angle and remove.
- **6.** Remove any remnants of food and foreign bodies in the area of the impeller.
- 7. Insert the pump cover ① and press down ②.
- The pump cover clicks into position.



8. Install the filter system.

Troubleshooting

	E:22 lights up. E:25 lights up.	Filters are soiled or blocked. ► Clean the filters. Wastewater pump is blocked. ► Clean the wastewater pump. Cover of the wastewater pump is loose ► Secure the cover of the Wastewater pump so it clicks into position.	Removable streaks are present on glasses, glass- ware with a metallic ap- pearance and cutlery. Rust spots on cutlery.	 Amount of rinse aid to be dispensed is set too high. Set the rinse aid system to a lower setting. No rinse aid has been added. Add rinse aid. Cutlery is not sufficiently rust-resistant. Knife blades are often 	
n on the water tap. ap is jammed or furred up. n on the water tap. flow rate must be at least 10 I/min when the water sup- s open.		 Clean the wastewater pump. Cover of the wastewater pump is loose Secure the cover of the Wastewater pump so it clicks into 	pearance and cutlery.	 Add rinse aid. 	
n on the water tap. flow rate must be at least 10 l/min when the water sup- s open.		 Secure the cover of the Wastewater pump so it clicks into 	Rust spots on cutlery.	Cutlery is not sufficiently rust-resistant. Knife blades are often	
		position.		Cutlery is not sufficiently rust-resistant. Knife blades are often more severely affected. • Use rust-resistant tableware.	
 ply is open. Filter in the water supply is blocked. 1. Switch off the appliance. 2. Pull out the mains plug. 3. Turn off the water tap. 4. Unscrew the water connection. 5. Remove the filter from the supply hose ply hose 6. Clean the filter. 7. Re-insert the filter in the supply hose. 8. Screw the water connection back on. 9. Check the water connection for leaks. 10. Restore the power supply. 	 Remnants of food on tableware. 	Tableware is placed too close together or basket is overfilled. 1. Arrange tableware with sufficient space in between.		Cutlery may also rust if washed together with rusting items. Do not wash rusting items.	
		The spray jets must reach the surfaces of the tableware. 2 Avoid points of contact.	Detergent residue is present in the detergent dispenser or the tablet collecting tray.	 Spray arms were blocked by tableware so detergent was not rinsed out. Check that the spray arms are not blocked and can rotate freely. 	
		 Spray arm rotation is blocked. Arrange tableware so that it does not obstruct spray arm rotation. 			
		Spray arm nozzles are blocked. ► Clean the Spray arms.			
		Filters are soiled. ► Clean the filters.			
		Filters are inserted incorrectly and/or not engaged. 1. Insert the filters properly. 2. Engage the filters.			
		 Washing programme selected too weak. ▶ Select a more intensive washing programme. 			
an the nose nose nsert ew th ck th tore t	the filter from the sup- the filter from the sup- e filter. the filter in the supply hose. e water connection back on. e water connection for leaks.	the filter from the sup- e filter. the filter in the supply hose. e water connection back on. e water connection for leaks. the power supply.	 the filter from the sup- the filter from the sup- the filter. the filter in the supply hose. the water connection back on. the water connection for leaks. the power supply. 	the filter from the sup- the filter from the sup- the filter. the filter. the filter in the supply hose. e water connection back on. e water connection for leaks. the power supply. the filter is the supply. the filter is the supply hose. the power supply. the filter is the filter is th	