

**Series 2, wall-mounted cooker hood,
60 cm, Stainless steel
DWP64CC50M**



DWA0KP6A Standard odor filter
DWZ6HP1U2 Standard recirculation kit

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom
in your kitchen planning.**

- **Silent:** maximal extractor performance with little noise
- **3-Speed Power Level Options To Suit Your Cooking Style And Recipes**

Typology:Wall-mounted
Length electrical supply cord: 120.0 cm
Height of the chimney: 410-765/410-765 mm
Height of product, without chimney: 250 mm
Net weight: 9.2 kg
Type of control:mechanical
Number of speed settings: 3
Max. air extraction:380 m³/h
Max. air recirculation: 235 m³/h
Number of lights: 2
Noise level: 64 dB(A) re 1 pW
Diameter of air outlet: 150 mm
Grease filter material:Washable aluminium
Odour filter: No
Operating Mode:Convertible
Optional accessories: DWA0KP6A, DWZ6HP1U2
Type of lamps used: LED
Total power of the lamps: 10 W
Grease filter type:Kassette
Connection rating: 135 W
Voltage: 220-240 V
Frequency: 50 Hz
Plug type: GB plug
Installation typology:Wall-mounted
Material body: Stainless steel
Plug type: GB plug
Dimensions of the product, with chimney (if exists) (in):x x
Dimensions of the packed product: 15.74 x 23.22 x 28.34
Net weight: 20.000 lbs
Gross weight: 32.000 lbs
Motor location: Integrated motor in hood body
No-return airflow flap: No
Length electrical supply cord: 120.0 cm
Dimensions of the product, with chimney (if exists): 790-1015 x
598.0 x 470.0 mm
Dimensions of the packed product (HxWxD): 400 x 590 x 720 mm
Net weight: 9.2 kg
Gross weight: 14.3 kg



Series 2, wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50M

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom
in your kitchen planning.**

Variant:

Design:

- Appliance colour: stainless steel
- Wall mounted hood

Comfort:

- Suitable for ducted or re-circulated extraction
- 3 speeds
- push buttons for extractor speeds and light
- Metal grease filter, dishwasher safe
- Charcoal filter

Environment and Safety:

- Energy Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 72.8 kWh/year*

Technical Info:

- Maximum extraction rate exhaust air 380 m³/h according to EN 61591
- Extraction rate in recirculation mode:
 - Max. normal use: 235 m³/h
- Noise min./max. Normal Level: 53/64 dB*
- Noise level in recirculation mode:
 - Max. normal use: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Power rating: 135 W
- Light Intensity: 1000 lux
- Colour Temperature: 4000 K

Measures:

- Electrical cable length 1.2 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 790 - 1015 x 598 x 470 mm
- Dimensions recirculating (HxWxD): 790 - 1015 x 598 x 470 mm

