

iQ700, Compact combination steam oven, Stainless steel CS658GRS1B



ncluded accessories

1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

Optional accessories

HZ636000	Glass pan
HZ632070	Multipurpose pan, anthracite enamelled
HZ632010	Universal pan, non-stick coated
HZ631070	Baking tray, anthracite enamelled
HZ625071	Grill tray, anthracite enamelled
HZ617000	Pizza pan, anthracite enamelled
HZ36D533P	porcelain tray-GN2/3- unpunched
HZ327000	Baking stone

The compact oven with fullSteam function and sensors for optimum results.

- ✓ TFT Touchdisplay Plus: optimum readability and intuitive operation.
- ✓ pulseSteam: for crispy crusts and juicy roasts.
- ✓ roastingSensor and bakingSensor: detect the exact moment when your food is done.
- ✓ ecoClean Plus: effortless cleaning thanks to a special coating.

/

Features

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Door opening : Drop down

Required niche size for installation (HxWxD) : $450-455 \times 560-568 \times 10^{-2}$

550

Dimensions of the product (mm): 455 x 594 x 548

Dimensions of the packed product (HxWxD) (mm) : $530 \times 660 \times 690$

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg) : 36.033 Approval certificates : CE, VDE

Length electrical supply cord (cm): 150

EAN code: 4242003671467

Current (A): 16 Voltage (V): 220-240 Frequency (Hz): 60; 50 Plug type: no plug

Approval certificates : CE, VDE Number of cavities (2010/30/EC) : 1

Usable volume (of cavity) - NEW (2010/30/EC): 47

Energy efficiency class (2010/30/EC): A+

Energy consumption per cycle conventional (2010/30/EC) : 0.73 Energy consumption per cycle forced air convection (2010/30/EC) :

0.61

Energy efficiency index (2010/30/EC): 81.3





iQ700, Compact combination steam oven, Stainless steel CS658GRS1B

Features

Design

- Cavity volume: 47 net usable litres
- Full Color TFT Touchdisplay Plus
- Electronic clock and timer
- Rotary Control
- Anthracite enamel cavity with 3 shelf levels
- LED lighting
- SoftMove oven door with soft open and soft close

Heating Functions

- Temperature range 30 °C 250 °C
- Compact steam oven with 15 heating methods:
- 4D HotAir
- 4D HotAir Eco
- Top/ bottom heating
- Top/bottom heating Eco
- Bottom heating
- Intensive heat
- Hot air grilling
- Full width grill
- Half width grillcoolStart (deep-frozen food special)
- Pizza setting
- Low temperature cooking
- Warming
- Plate warming setting
- Drying
- Rapid heating-up
- Additional heating methods with steam: Pure steaming, Reheating, Dough Proving, Defrost

Sensor and Automatic Functions

- roastingSensor with three measuring points
- bakingSensor
- Meals (automatic programs)

Convenience

- Info button
- 1 level telescopic shelf, 3 level telescopic shelf rails full extension, safety stop function
- Large 1 litre water tank
- Water tank empty indicator
- Temperature proposal
- Actual temperature display
- Actual temperature display
- Sabbath setting

Cleaning

- EcoClean Direct : back panel, ceiling, side liners
- ecoClean® self-cleaning function (rear, sides and ceiling)
- Additional functions:
- Descaling programme
- Drying function

Safety and Environment

- Triple glazed door with heat reflective glass
- Child lock for settings
- Residual heat indicator
- Automatic safety switch-off function

• Integrated cooling fan

Technical Info

- Appliance dimensions (HxWxD): 455 mm x 595 mm x 548 mm
- Installation dimensions (HxWxD): 450 mm 455 mm x 560 mm 568 mm x 550 mm
- Total connected load electric: 3.3 KW
- Length of mains cable: 120 cm
- "Please reference the built-in dimensions provided in the installation drawing"


Accesorie


- 1 x grid, 1 x Steam container, punched, size XL, 1 x Steam container, punched, size S, 1 x Steam container, unpunched, size S, 1 x universal pan
- •
- .
- •





iQ700, Compact combination steam oven, Stainless steel CS658GRS1B

Dimensioned drawings









If the compact appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness		
	fitted	flush	
Induction hob	42 mm	43 mm	
Full surface Induction hob	52 mm	53 mm	
Gas hob	32 mm	43 mm	
Electric hob	32 mm	35 mm	