

Series 2, Wall-mounted canopy rangehood, 60 cm, Stainless steel DWB65BC50A



DWZ0FB5K0 Chimney extension 1000 mm
DWZ6DE1A2 Standard odor filter

Canopy rangehood: performance and matching kitchen design bundled in one rangehood.

- **Metal Grease Filter:** cleans the air, captures grease, easy monthly clean-up.
- **3-Speed Power Level Options To Suit Your Cooking Style And Recipes**

Color chimney:Stainless steel
Typology:Wall-mounted
Length electrical supply cord: 150.0 cm
Height of the chimney: 415-680/495-770 mm
Height of product, without chimney: 53 mm
Minimum distance above an electric cooktop: 600 mm
Minimum distance above a gas cooktop: 750 mm
Net weight: 11.2 kg
Type of control: mechanical
Number of power settings: 3
Max. air extraction: 612 m³/h
Max. air recirculation: 273 m³/h
Number of lights: 2
Noise level: 69 dB(A) re 1pW
Diameter of air outlet: 120 mm
Grease filter material: Washable aluminium
EAN code: 4242005184941
Connection rating: 216 W
Voltage: 220-240 V
Frequency: 50 Hz
Plug type: AU plug
Installation typology: Wall-mounted



4 242005 184941

Series 2, Wall-mounted canopy rangehood, 60 cm, Stainless steel DWB65BC50A

**Canopy rangehood: performance and
matching kitchen design bundled in one
rangehood.**

Design & Innovation

- Box design
- Appliance colour: Stainless steel
- Accessory required for recirculation mode: Standard recirculation kit

Power and Mode of Operation

- 3 power settings
- Push button for power and light
- Extraction rate exhaust air according to EN 61591: max. 612 m³/h
- Extraction rate in recirculation mode: Max. normal use: 273 m³/h
- Suitable for ducted or re-circulated extraction
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Noise level in recirculation mode:
- Max. normal use: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)

Convenience

- 2 x 3 Watt LED Lights
- Dishwasher safe Metal grease filters
- Noise min./max. Normal Level: 49/69 dB

2 year warranty

Technical Information

- Appliance width: 600 mm
- Dimensions exhaust air (HxWxD): 550-830 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 550-830 x 600 x 500 mm
- Energy Efficiency Class: C (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 91 kWh/year
- Diameter pipe Ø 120 mm (Ø 120 mm enclosed)
- Power rating: 216 W
- Electrical cable length 1.5 m

The diagram illustrates the required clearances for a kitchen hood installation. Key dimensions and labels include:

- 45**: Clearance between the hood and the countertop.
- (B)**: Label for the side clearance dimension.
- 250**: Width of the hood.
- ≥ 392** : Minimum clearance between the hood and the ceiling.
- ≥ 550 electric** and **≥ 650 gas**: Minimum clearances from the hood to the cooktop, depending on the fuel type.
- (A)**: Label for the front clearance dimension.

Technical drawing of a table with a central pedestal and a cylindrical object on top. Dimensions are given in millimeters: total height 382, height to top of pedestal 346, and pedestal height 20.

A 3D perspective diagram of a multi-story building. The building has a sloped roof on the left side. Dimensions are indicated with arrows and numbers: 45 (width of the sloped roof section), 188 (height of the main building body), 170 (height of the upper section), 286 (total height from the ground level to the top of the main body), 680 (width of the building body), and 34 (height of the ground level section). The building is labeled with (A). Below the building, there is a rectangular area with four circles inside, representing a pool or a courtyard. To the left of the building, there is text: ≥ 550 electric and ≥ 650 gas.

3 /