

iQ500, Modular Teppan yaki, 40 cm ET475FYB1E





Included accessories

2 x spatula

Optional accessories

HZ394301 Connecting strip

The Domino teppanyaki cooktop for preparing light, low-fat dishes the typical Japanese way.

- ✓ The 40 cm wide teppanyaki is ideal for combining with other Domino or faceted design cooktops.
- ✓ touchSlider control allows to control the temperature by entering it directly or by moving the slider with a single finger.
- ✓ Depending on the requirements and quantities the two cooking zones can be heated together or seperately.
- ✓ Tastefully integrated into the Domino unit when not in use, thanks to the high-quality glass ceramic cover.
- ✓ Heats to 40°C so that grease deposits can be removed more easily.

Features

Technical Data

Product name/family: Vario/Domino Teppan Yaki

Built-in / Free-standing : Built-in Energy input : Electric Type of control : Electronic Grill grating material : N/A

Required niche size for installation (HxWxD): 90 x x

Width of the appliance : 392 Dimensions : 90 x 392 x 520

Dimensions of the packed product (HxWxD) (mm): 240 x 480 x 610

Net weight (kg): 10.231 Gross weight (kg): 12.3 Residual heat indicator: Separate Location of control panel: Hob front Basic surface material: N/A

Color of surface : Alu, brushed, Stainless steel

Approval certificates: Australia Standards, CE, Eurasian, Ukraine, VDE

Length electrical supply cord (cm): 100

EAN code: 4242003689127

Electrical connection rating (W): 1900

Current (A) : 13 Voltage (V) : 220-240 Frequency (Hz) : 50; 60





iQ500, Modular Teppan yaki, 40 cm ET475FYB1E

Features

Design

- Black ceramic glass with stainless steel side profiles and beveled front
- Can be combined with Domino cooktops
- Removable black glass lid

Comfort & Convenience

- LED display and timer with auto switch off
- Keep warm function
- Special level for cleaning (40°C)
- Count-up timer, LED display and timer with auto switch off
- ReStart Quickly reinstates previous settings
- 2 spatulas included

Safety and Environment

- Power on indicator light
- Heat up phase display
- 2-stage (h/H) digital residual heat indicator
- wipeProtection function Quickly pauses settings to clean as you go
- Energy consumption display


Dimensions (WxD)


- Installation measurements: 360 mm x 490 mm
- Length wire connection: 100 cm
- Min. worktop thickness: 30 mm




iQ500, Modular Teppan yaki, 40 cm ET475FYB1E


Dimensioned drawings






When installing two or more Domino units side-by-side, one or more assembly kits are required (2 units = 1 assembly kit, 3 units = 2 assembly kits, etc.).





When installing two or more Domino units side-by-side, one or more assembly kits are required (2 units = 1 assembly kit, 3 units = 2 assembly kits, etc.).

Width category: Appliance width:	30 40 60 70 80 90 302 392 602 710 812 91					
	I A	В	C	D	L	×
2x30	302	302			604	577
1x30, 1x40	302	392		-	694	663
1x30, 1x60	302	602			904	877
1x30, 1x70°	302	710			1012	980
1x30, 1x80	302	812			1114	1082
1x30, 1x90	302	912			1214	1182
2x40	392	392			784	750
1x40, 1x60	392	602			994	963
1x40, 1x70°	392	710			1102	1071
1x40, 1x80	392	812			1204	1177
1x40, 1x90	392	912			1304	1277
3x30	302	302	302		906	874
2x30, 1x40	302	302	392		996	964
2x30, 1x60	302	302	602		1206	1174
2x30, 1x70°	302	302	710		1314	128
2x30, 1x80	302	302	812		1416	1384
2x30, 1x90	302	302	912		1516	148
1x30, 2x40	302	392	392		1086	105
1x30, 1x40, 1x60	302	392	602		1296	126
1x30, 1x40, 1x70	302	392	710		1404	1377
1x30, 1x40, 1x80	302	392	812		1506	147
1x30, 1x40, 1x90	302	392	912		1606	157
3x40	392	392	392		1176	114
2x40, 1x60	392	392	602		1386	135
4x30	302	302	302	302	1208	117
3x30, 1x40	302	302	302	392	1298	126
2x30, 2x40	302	302	392	392	1388	1358
1x30, 3x40	302	392	392	392	1478	144



- A: Minimum distance from the hob cut-out to the wall
- to the wall B: Maximum recessed depth