

**iQ700, Integrated rangehood, 86 cm,
Stainless steel
LB89584AU**



The powerful canopy rangehood is concealed above the cooktop.

- ✓ The highly efficient 820 m³/h extraction rate provides ideal air quality in the kitchen.
- ✓ The energy saving LED lighting with dimmer function ensures ambient lighting and optimal visibility when cooking.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert to previous setting after 6 min.
- ✓ Whisper quiet operation: only 55 dB (400 m³/h) - 150mm ducted.

Features

Technical Data

Typology : Traditional
Approval certificates : Australia Standards, CE, VDE
Length electrical supply cord (cm) : 150
Required niche size for installation (HxWxD) : 418mm x 836.0mm x 264mm
Minimum distance above an electric hob : 500
Minimum distance above a gas hob : 650
Net weight (kg) : 12.979
Type of control : Electronic
Maximum output air extraction (m³/h) : 610
Boost position output recirculating (m³/h) : 370.0
Boost position air extraction (m³/h) : 820
Number of lights : 2
Noise level (dB) : 64
Diameter of air outlet (mm) : 150 / 120
Grease filter material : Washable aluminium
EAN code : 4242003700877
Connection Rating (W) : 272
Current (A) : 3
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : AU plug
Installation typology : Built-in

Optional accessories

| | |
|---------|------------------------------------|
| LZ55750 | Standard recirculation kit |
| LZ55651 | Standard odor filter (replacement) |
| LZ46810 | CleanAir active carbon filter |



**iQ700, Integrated rangehood, 86 cm,
Stainless steel
LB89584AU**

Features

Design & Innovation

-
-
- Appliance colour: Stainless steel
- Electronic controls with low-lift push buttons
- 2 x 1 Watt LED lights
- metal grease filters with stainless steel cover

Convenience

- For installation in a kitchen cabinet
- Electronic controls
- Saturation display for filters

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 610 m³/h
- Intensive 820 m³/h
- 3 power levels plus intensive setting
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on time - 30 min
- Rim ventilation
- Twin channel high performance fan motor
- Suitable for ducted and re-circulating operation

Cleaning

- Dishwasher safe metal grease filters
- Cassette with alu frame

Safety and Quality

- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 64 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Intensive: 71 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)

Dimensions (HxWxD)

- Power rating: 272 W
- Dimensions - Recirculated with cleanAir module (HxWxD):
- NO_FEATURE x 860 x 282 mm
- Accessories required for recirculation mode: CleanAir Module
- Front profile décor strip or pelmet required (not supplied with rangehood)
- 850bldc
- 120 or 150 mm tube connection diameter
- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)