

iQ700, Wall-mounted canopy rangehood, 90 cm, Stainless steel LC91BUV50B



The wall hood convinces with a very high extraction rate in a distinguished design that perfectly matches your kitchen.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Home Connect – The app that makes your hood work smarter.
- ✓ LED light: Optimal visibility and atmosphere when cooking.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert to previous setting after 6 min.
- ✓ voiceControl : Control hood functions using your voice.

LZ00XP00	Long Life odor filter (replacement)
LZ10FXJ05	Long Life recirculation kit
LZ11CXI16	Clean Air Plus recirculation kit
LZ12265	Chimney extension 1000 mm
LZ12365	Chimney extension 1500 mm
LZ12CBI14	Clean Air Standard recirculation kit
LZ12CXC56	Clean Air Plus recirc. kit external
LZ12FXD51	Long Life recirculation kit external
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ32CBB14	Clean Air Standard odor filter (repl.)
LZ50960	Backboard 90x65cm
LZ50961	Backboard 90 x 72 cm

Typology: Wall-mounted
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 582-908/568-1018 mm
 Height of product, without chimney:46 mm
 Minimum distance above an electric cooktop: 600 mm
 Minimum distance above a gas cooktop: 650 mm
 Net weight: 18.8 kg
 Type of control: Electronic
 Number of power settings: 3-stages + 2 intensive settings
 Max. ducted extraction: 602 m³/h
 Boost position output recirculating:561 m³/h
 Max. recirculation:462 m³/h
 Boost position air extraction:965 m³/h
 Number of lights:3
 Noise level:64 dB(A) re 1pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable stainless steel
 EAN code:4242003832011
 Power supply: 265 W
 Fuse protection: 10 A
 Voltage:220-240 V
 Frequency:50; 60 Hz
 Plug type: GB plug
 Installation type: Wall-mounted



iQ700, Wall-mounted canopy rangehood, 90 cm, Stainless steel LC91BUV50B

Design & Innovation

- Wall mounted rangehood
- Appliance colour: Stainless steel
- touchControl for power and light
- Efficient BLDC technology

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 602 m³/h. Intensive 965 m³/h
- Noise min./max. Normal Level: 45/64 dB
- touchControl (3 power levels + 2 intensive levels) with LED display
- Boost function
- Intensive operation automatic revert - 6min
- With the Clean Air Plus recirculation kit (available as accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use:462m³/h
 - Intensive:561m³/h
 - Noise level in recirculation mode: Max. normal use:68dB(A) re 1 pW
 - Intensive:72 dB(A) re 1 pW

Cleaning

- Dishwasher safe metal grease filters
- Saturation display for filters
- Stainless steel filter covers, dishwasher safe

Safety and Quality

- 3 x 1.5 Watt LED Lights
- softLight with Dimming function
- climateControl sensor automatically adjusts the rangehood power level to the steam and odours
- Automatic run on - 10 min

Convenience

- Suitable for ducted and re-circulating operation
- Accessory required for recirculation mode: Standard recirculation kit
- Sound insulation mats for optimised sound absorption
- cooktop-based rangehood control (with matching cooktop)
- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet
- Voice Control enabled via popular voice assistants
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)

Dimensions (HxWxD)

- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
 - 689 x 898 x 500mm - mounting with outer chimney
 - Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

Technical Information

- Power rating: 265 W

- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

