

**Series 2, Integrated cooker hood, 60 cm, Silver
DEM66AC00B**



DWZ0IM0A0 Standard odor filter (replacement)

B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- **High extraction rate - for continuously clean air in the kitchen.**
- **3-speed power Level options to suit your cooking style and recipes.**
- **Ducted or Non-ducted Options**

Typology: Built-in/Built-under
 Length electrical supply cord: 150.0 cm
 Minimum distance above an electric hob: 500 mm
 Minimum distance above a gas hob:650 mm
 Net weight: 10.8 kg
 Type of control:mechanical
 Number of speed settings: 3
 Max. air extraction: 625 m³/h
 Max. air recirculation: 416 m³/h
 Maximum Air flow: 625 m³/h
 Number of lights: 2
 Noise level:70 dB(A) re 1pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material:Washable aluminium
 EAN code:4242005041121
 Connection rating: 256 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation typology:Wall-mounted



Series 2, Integrated cooker hood, 60 cm, Silver DEM66AC00B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- Push button control for extractor speeds and light
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 removable metal grease filter cassettes

Design

- Integrated hood
- Installation: Between Cupboards
- Push button control
- Mechanical

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 68.4 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

Optional accessories

- Recirculating kit DWZ01M0A0

* In accordance with the EU-Regulation No 65/2014

**Series 2, Integrated cooker hood, 60
cm, Silver
DEM66AC00B**

