



iQ700, Flex induction cooktop, 30 cm, surface mount with frame EX375FXB1E



Siemens flexInduction cooktop is designed for greater flexibility when cooking

- ✓ The 30 cm wide cooktop is ideal for combining with other Domino or faceted design cooktops.
- ✓ flexInduction – Smart cooking zone that adapts to your cookware.
- ✓ Allows to control the temperature by entering it directly or by moving the slider with a single finger - touchSlider Control.
- ✓ powerMove Plus enables intuitive control thanks to three heating zones with different temperatures, just by moving the pan
- ✓ powerBoost – Increases the power of an induction zone by up to 50%.

Features

Technical Data

Product name/family: Vario/Domino cooking zone cera
Built-in / Free-standing: Built-in
Source of energy: Electric
Number of cooking zones: 2
Required niche size for installation (HxWxD): 51 x 270 x 490-500 mm
Width of the appliance: 302 mm
Dimensions: 51x302x520 mm
Dimensions of the packed product (HxWxD): ... 126 x 383 x 597 mm
Weight: 8.1 kg
Gross weight: 8.7 kg
Residual heat indicator: Separate
Location of control panel: Front
Basic surface material: Ceramic
Color of surface: Black, Alu, brushed
Length electrical supply cord: 110.0 cm
EAN code: 4242003697405
Nominal power: 220-240 V
Frequency: 60; 50 Hz



Optional accessories

HZ32WA00 Wireless food thermometer, HZ390011 Stainless Steel roaster with glas lid, HZ390012 Steaming Rack for Stainless Steel roaste, HZ390090 Wok Set consisting of 3 Items, HZ390512 Teppan Yaki (large), HZ390522 Griddle Plate, HZ394301 Connecting strip, HZ9ES100 Espresso maker 4 cups, HZ9FE280 Iron pan Ø 18 / 28 cm, HZ9FF010 Flex Pan, large, HZ9FF030 Flex Pan set, 3 pcs., HZ9FF040 Flex Pan set, 4 pcs., HZ9SE030 Set of 2 pots and 1 pan, HZ9SE040 4 pieces Set, HZ9SE060 6 pieces Set, HZ9TY010 Teppan Yaki

iQ700, Flex induction cooktop, 30 cm, surface mount with frame EX375FXB1E

Features	
<p>Design</p> <ul style="list-style-type: none">• Stainless Steel side trim with bevelled front edge• 30 cm: space for 2 pots or pans. <p>Flexibility of cooking zones</p> <ul style="list-style-type: none">• flexInduction zone: use cookware of any shape or size anywhere within the 40cm long zone.• Cooking zone middle: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)• Cooking zone middle: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW) <p>Usage convenience</p> <ul style="list-style-type: none">• touchSlider: directly control the power with imprinted touch bar.• 17 power levels: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).• Timer for all zones• : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).• Acoustic signal• : an alarm sounds at the end of the time set (e.g. for pasta).• Count up timer• : shows how much time has passed since starting the timer (e.g. for potatoes). <p>Time saving & efficiency</p> <ul style="list-style-type: none">• Power boost setting• : boil water faster thanks to 50% more energy than at the highest standard level.• powerMove plus: increase or decrease the power level simply by moving the pot forwards or backwards.• quickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).• reStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds. <p>Safety</p> <ul style="list-style-type: none">• 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.• Control panel lock: prevent unintended activation of the hob.• Control panel pause: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).• Main on/off switch: switch off all cooking zones at the touch of a button.• Automatic safety switch off: for safety reasons, heating stops after a preset time if not used.• Energy Consumption Display: shows the electricity consumption of the last cooking process. <p>Installation</p> <ul style="list-style-type: none">• Dimensions of the product (HxWxD mm): 51 x 302 x 520• Required niche size for installation (HxWxD mm) : 51 x 270 x (490 -	<p>500)</p> <ul style="list-style-type: none">• Min. worktop thickness: 16 mm• Connected load: 3.7 KW• Connection current management (20, 16, 13, 10 Amps options): limit the maximum power if needed (depends on fuse protection of electric installation).• Power cord: 1.1 m, Cable included

iQ700, Flex induction cooktop, 30 cm, surface mount with frame EX375FXB1E

Dimensioned drawings

Measurements in mm

L	X
302	874
392	964

If two or more elements are installed right next to one another, one or several installation kits are required (2 elements 1 installation kit, 3 elements 2 installation kits, etc.)

Measurements in mm

measurements in mm

A: Minimum distance from the hob cut-out to the wall.
B: Recessed depth
C: The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space requirements for the oven.





The worktop into which the hob is installed must withstand loads of approx. 60 kg; suitable substructures must be used if required.

D	E	F
585-600	50	≥ 35
> 600	≥ 50	≥ 50

① Ventilation gap must be present.


Measurements in mm

Dimensioned drawings



Dimensioned drawings

Measurements in mm
Assembly kit (HZ394301) for Domino




B: Dependent on the cut-out depth

measurements in mm
Domino combination options with corresponding
appliance and cut-out dimensions

Width category:	30	40	60	70	80	90
Appliance width:	302	392	602	710	812	912
	A	B	C	D	L	X
2x30	302	302	-	-	604	572
1x30, 1x40	302	392	-	-	694	662
1x30, 1x60	302	602	-	-	904	872
1x30, 1x70*	302	710	-	-	1012	980
1x30, 1x80	302	812	-	-	1114	1082
1x30, 1x90	302	912	-	-	1214	1182
2x40	392	392	-	-	784	752
1x40, 1x60	392	602	-	-	994	962
1x40, 1x70*	392	710	-	-	1102	1070
1x40, 1x80	392	812	-	-	1204	1172
1x40, 1x90	392	912	-	-	1304	1272
3x30	302	302	302	-	906	874
2x30, 1x40	302	302	392	-	996	964
2x30, 1x60	302	302	602	-	1206	1174
2x30, 1x70*	302	302	710	-	1314	1282
2x30, 1x80	302	302	812	-	1416	1384
2x30, 1x90	302	302	912	-	1516	1484
1x30, 2x40	302	392	392	-	1086	1054
1x30, 1x40, 1x60	302	392	602	-	1296	1264
1x30, 1x40, 1x70*	302	392	710	-	1404	1372
1x30, 1x40, 1x80	302	392	812	-	1506	1474
1x30, 1x40, 1x90	302	392	912	-	1606	1574
3x40	392	392	392	-	1176	1144
2x40, 1x60	392	392	602	-	1386	1354
4x30	302	302	302	302	1208	1176
3x30, 1x40	302	302	302	392	1298	1266
2x30, 2x40	302	302	392	392	1388	1356
1x30, 3x40	302	392	392	392	1478	1446
1x30, 1x75	302	750	-	-	1052	1016
1x40, 1x75	392	750	-	-	1142	1106
2x30, 1x75	302	302	750	-	1354	1318
1x30, 1x40, 1x75	302	392	750	-	1444	1408

* Not possible with 70 cm induction hob

Measurements in mm
Picture for the table Domino combination possibilities with corresponding devices and
cutout dimensions



If two or more elements are installed right next to one another, one or several installation kits are required (2 elements 1 installation kit, 3 elements 2 installation kits, etc.)

Cutout dimension (X) depending on the combination (see combination table)