Color Variants

GV451120

Included accessories

50 x vacuuming bag. small.

50 x vacuuming bag. big.

1 x raised vacuuming platform.

1 x adaptor f. vacuuming outside the chamber.

1 x vacuuming hose.

Built-in / Free-standing Built-in

Maximum number of plates

Characteristics

Maximum number of espresso cups

Dimensions

140x594x519

Dimensions of the packed product (HxWxD)

240 x 660 x 670

Required niche size for installation (HxWxD)

140 x 560 x 550

EAN code

4242006313197

Fuse protection

Voltage

220-240

Frequency

Plug type

Gardy plug w/ earthing

Included accessories

50 x vacuuming bag, small, 50 x $\,$ vacuuming bag, big, 1 x raised vacuuming platform, 1 x adaptor f. vacuuming outside the chamber, 1 x vacuuming hose, 1 x adaptor for bottle plugs, $3\ x$ plugs for vacuuming of bottles

Consumption and connection features

created on 2025-08-23

Page 1

Highlights

Integrable in 14 cm high niche Hygienic stainless steel vacuuming chamber, applicable height up to 95

3 vacuuming levels for vacuuming in the chamber, max. 99% 3 vacuuming levels for vacuuming outside the chamber, max. 90% Automatic connection recognition for vacuuming outside the chamber Handleless drawer Push-to-open function.

Application

Vacuuming for sous-vide cooking. Vacuuming for fast marinating and flavouring.

Vacuuming for fast marinating and flavouring.

Vacuuming of vacuuming containers outside the chamber.

Vacuuming of liquids in bottles outside the chamber.

Handling

Touch key operation.

Net volume 7 litres. Capacity load max. 10 kg. Maximum size of vacuuming bags W 240 mm x L 350 mm.

3 heat-sealing levels for different strengths of bag material. Sealing bar, non-stick coating, removable.

Safety glass cover, opens automatically after vacuuming.

Raised vacuuming platform, 44 mm, deployable.

Utility space in vacuuming chamber, W 210 mm x L 275 mm.

Membrane for avoiding reflow of liquids during vacuuming outside the chamber. Drying programme for vacuuming pump.

Planning notes

shelf.

Plan the niche without back wall. Protrusion from appliance front to furniture cabinet 42 mm. Installation of GO/GS/GM/GC directly above the drawer without intermediate

Installation directly above a dishwasher is not allowed.


The socket can be planned behind the

Special accessories (order as spare parts):

Part No. 00578813 vacuuming bags, small Part No. 00578814 vacuuming bags, big.

Total connected load 0.32 KW. Connection cable 1.50 m, pluggable.





GAGGENAU