iQ700, Built-in oven with added steam and microwave function, 60 x 60 cm, Black HN878G4B6B









2 x combination grid, 1 x universal pan

HZ327000 Baking stone, HZ531010 Baking tray, non-stick ceramic coated, HZ532010 Universal pan, non-stick ceramic coated, HZ617000 Pizza pan, enamelled, HZ625071 Grill tray, enamelled, HZ631070 Baking tray, enamelled, HZ632070 Multipurpose pan, enamelled, HZ633001 Lid for professional pan, enamelled, HZ633070 Professional pan, enamelled, HZ634080 Baking and roasting grid (microwave), HZ636000 Glass pan, HZ664000 Baking and roasting grid (steam), HZ66X650 Cover Strip, HZ6BMA00 Assembly kit for vertical installation, HZ915003 Glass roasting dish, 5,4 L

Shorten your cooking time thanks to varioSpeed, fast preheat and activeClean. And remote your oven from anywhere with Home Connect.

- ✓ varioSpeed Prepare excellent dishes up to 50% faster.
- √ fastPreheat Heat the oven quickly. coolStart Eliminate preheating for frozen foods.
- ✓ activeClean® The automatic, self-cleaning oven system.
- ✓ pulseSteam: for crispy crusts and juicy roasts.
- ✓ Home Connect Experience the intelligent kitchen via app.

Additional functions:	Microwave	
combination oven		
Control panel:	Electronic	
Dimensions:	595 x 594 x 548 mm	
Cavity dimensions:	357.0 x 480 x 392.0 mm	
Length electrical supply cord:	120.0 cm	
Weight:	49.2 kg	
Gross weight:		
EAN code:	4242003789858	
Maximum micro-wave power:	800 W	
Connection Rating:	3600 W	
Fuse protection:	16 A	
Nominal power:	220-240 V	
Frequency:	60; 50 Hz	
Plug type:	no plug	
(electrical connection by electrician)		
Included accessories: 2 x combin	ation grid, 1 x universal pan	



iQ700, Built-in oven with added steam and microwave function, 60 x 60 cm, Black HN878G4B6B

Design

- 5.7" TFT touchDisplay Plus
- Cavity inner surface: enamel anthracite
- Drop down oven door, softClose, softOpen
- studioLine Black Steel Design
- Stainless steel control dial
- We recommend you to choose complementary products within IQ700, in order to assure an optimal design combination of your Built-In appliances.

Features

- Intelligent microwave inverter technology: For optimised results maximum output power will be regulated to 600 W when used in longer operation for gentler cooking.
- Digital temperature display with proposal
- Actual temperature display Heating-up indicator Temperature probe
- Electronic door lock
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- WLAN Home connect enabled
- cookControl Plus
- bakingSensor
- roastingSensor Plus
- Electronic oven clock timer
- Multilevel LED Illumination, LED light, Light on/off when door opened/closed
- Tank empty indicator
- Integral cooling fan
- 5 shelf positions in oven

Cleaning

• activeClean

Programmes/functions

- Oven with microwave with 15 PC heating methods: 4D hot air, hotairGentle, conventional top & bottom heating, Conventional heat Gentle, hot air grilling, full width grill, half width grill, Pizza setting, coolStart, bottom heat, intensive conventional heat, low temperature cooking, keep warm, dehydrate, plate warming
- Additional heating methods with steam: reheating with steam, Dough proving
- Additional heating methods with microwave: Microwave, Combi microwave variable, Dough proving, reheating with steam
- Fast preheat

Accessories


- 1 level telescopic shelf, pyrolitic proof
- 2 x combination grid, 1 x universal pan

Technical information

- Cavity volume: 67 litres
- \bullet Temperature range 30 °C 275 °C

- · Location of water tank: Outside cavity
- Total connected load electric: 3.6 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x
- Please refer to the dimensions provided in the installation manual

iQ700, Built-in oven with added steam and microwave function, 60 x 60 cm, Black HN878G4B6B



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

min. worktop thickness	
fitted	flush
37 mm	38 mm
47 mm	48 mm
30 mm	38 mm
27 mm	30 mm
	fitted 37 mm 47 mm

