

Series 6, Free-standing fridge-freezer with freezer at bottom, 201 x 70 cm, Brushed steel anti-fingerprint KGE49AICAG



The bottom freezer with VitaFresh 0 °C Box: keeps your meat and fish fresher for longer

- **VitaFresh:** keeps food fresh for longer in climate-controlled drawers at around 0°C.
- **LED lighting:** all your items in perfect view.
- **Big Box drawer:** easily stack food containers and store larger items in your freezer.
- **Easy Access Shelf:** a pull-out glass shelf for easier access to everything inside your fridge.
- **Low Frost:** defrost less often thanks to reduced frost – saving time, effort and energy.

Energy Efficiency Class:	C
Average annual energy consumption in kilowatt hour per year (kWh/a):	163 kWh/annum
Sum of volume of frozen compartments:	117 l
Sum of volume of chill compartments:	302 l
Airborne acoustical noise emissions :	38 dB(A) re 1pW
Airborne acoustical noise emission class:	C
Built-in / Free-standing:	Freestanding
Door panel options:	Not possible
Height:	2010 mm
Width of the appliance:	700 mm
Depth:	650 mm
Net weight:	84.8 kg
Connection rating:	90 W
Fuse protection:	10 A
Door hinge:	Right reversible
Voltage:	220-240 V
Frequency:	50 Hz
Length electrical supply cord:	240.0 cm
Number of compressors:	1
Number of independent cooling systems:	2
Interior ventilator:	Yes
Reversible Door Hinge:	Yes
Number of Adjustable Shelves in fridge compartment:	2
Shelves for Bottles:	Yes
Frost free system:	No
Installation typology:	Free-standing

KSZ10010 Snackbox



Series 6, Free-standing fridge-freezer with freezer at bottom, 201 x 70 cm, Brushed steel anti-fingerprint KGE49AICAG

The bottom freezer with VitaFresh 0 ° C Box: keeps your meat and fish fresher for longer

- KGE49AICAG
- Fridge freezer

Functions

- stainless steel look doors and Pearl grey (VZF 07127) side panels
- Integrated vertical handle
- Bright interior LED fridge light in fridge section

Design features

- Electronic control for fridge and freezer with LED display
- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity
- Acoustic alarm
- optical and acoustical warning system with failure memory function, optical and accoustical
- Holiday mode
- Super Cooling: automatic deactivation
- Automatic defrost fridge

Design features

- 5 removable safety glass shelves of which 2 are easy pull out
- Door shelves in fridge door: 1 large and 3 small.
- Metal bottle rack

Freshness System

- Capacity in 0° C section: 28 l
- 1 VitaFresh drawer - Fish and meat stay fresh for longer, 1 CrisperBox - vegetable/salad container with humidity control
- 1 CrisperBox - vegetable/salad container with humidity control

Food freshness system

- LowFrost - less ice creation and therefore quicker defrosting
- 3 transparent freezer drawers, including 1 BigBox

Dimension and installation

- Dimensions: 201 cm H x 70 cm W x 65 cm D

Key features - Fridge section

- Right hinged door, door reversible
- Height adjustable front feet
- Defrost water outlet - for easy and convenient defrosting
- Connection value 90 W
- 220 - 240 V

Key features - Freezer section

- 3 x egg tray

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the distanceholders

have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.

Additional features


Design features

Dimension and installation

Performance and Consumption

- EU19_EEK_D: C
- Total Volume : 419 l
- Net Fridge Volume : 302 l
- Net Freezer Volume : 117 l
- Freezing capacity 24h : 6.5 kg
- Annual Energy Consumption: 163 kWh/a
- Climate Class: SN-T
- EU19_Fast freezer facility_D
- Noise Level : 38 dB , EU19_Noise emission class_D: C
- Temperature rise time : EU19_Temperature rise time_D: 20 H

**Series 6, Free-standing fridge-freezer
with freezer at bottom, 201 x 70 cm,
Brushed steel anti-fingerprint
KGE49AICAG**



Device name	a	b	c	d	e	f	g	h
KGV39/KGE39 (inner handle)	2010	600	650	580	600	1200	650	690
KGV39/KGE39 (outer handle)	2010	600	650	580	640	1200	690	690
KGE49 (inner handle)	2010	700	650	580	700	1300	650	690
KGE49 (outer handle)	2010	700	650	580	740	1300	690	690

Specification

a Height
b Width
c Depth with door closed, without handle and without flexible spacing piece
d Cabinet depth without flexible spacing piece
e Width with door opened to 90°
f Depth with door opened, without handle and without flexible spacing piece
g Depth with door closed, with handle and without flexible spacing piece
h Depth with door closed, without handle and with flexible spacing piece

measurements in mm