iQ500, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, flat hinge KI87SAFE0G

A ↑ G





KS10Z020	Bottle Rack
KSGGZM00	Butter box



built-in fridge freezer, with lowFrost technology and hyperFresh plus Box to keep produce fresh up to twice as long.

- ✓ hyperFresh plus: keeps fruit and vegetables fresher for longer.
- ✓ lowFrost Less frost build-up saves energy and effort when defrosting.
- ✓ LED light Even lighting throughout the inside of your fridge to keep everything in view.
- ✓ The bigBox offers plenty of space to store and stack large frozen items efficiently.
- The easyAccess glass shelves make loading easier and give you a better view of your food items.

	_
Energy Efficiency Class:E	
Average annual energy consumption in kilowatt hour per year	
(kWh/a):	
Sum of volume of frozen compartments:	
Sum of volume of chill compartments:	
Airborne acoustical noise emissions :	
Airborne acoustical noise emission class:	
Built-in / Free-standing:	
Door panel options:	Not possible
Height:	
Width of the appliance:	558 mm
Dimensions:	545 mm
Required niche size for installation (HxWxD): .1	775 x 560 x 550 mm
Weight:	62.9 kg
EAN code:	4242003858523
Connection Rating:	90 W
Fuse protection:	13 A
Door opening:	Right reversible
Nominal power:	220-240 V
Frequency:	50 Hz
Length electrical supply cord:	230.0 cm
Number of compressors:	1
Number of independent cooling systems:	2
Interior ventilator:	No
Reversible Door Hinge:	Yes
Number of Adjustable Shelves in fridge compartment:	
Shelves for Bottles:	
Frost free system:	Not applicable
Installation type:	Fully integrated





iQ500, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, flat hinge KI87SAFE0G

Functions

• Bright interior LED fridge light in fridge section

Design features

- LED display for fridge and freezer
- VitaControl constant temperature by intelligent sensor technology -Constant temperature control by intelligent sensor technology
- Twin evaporators allows independent temperature control and ensures there is no transference of humidity between the fridge and
- Super Cooling: automatic deactivation
- Super Cooling: automatic deactivation
- SuperFreeze with Manual/automatic activiation
- Holiday mode
- Acoustic open door warning system
- Freezer malfunction warning signal: Optical and acoustical

Design features

- 5 safety glass shelves (4 height adjustable)
- 5 door trays, including 1x dairy compartment

Freshness System

• 1 hyperFresh plus box with adjustable humidity - keeps fruit and vegetables fresh for longer.

Food freshness system

- lowFrost less ice creation and therefore quicker defrosting
- Removable safety glass shelves for extra space
- 2 transparent freezer drawers, 1 bigBox

Dimension and installation

- Dimensions: 177.2 cm H x 55.8 cm W x 54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

Key features - Fridge section

- Right hinged door, door reversible
- Connection value 90 W
- 220 240 V
- Transportation handles

Key features - Freezer section

- KI87SAFE0G
- bottle holder in door tray

Value ad

- lowFrost less ice creation and therefore quicker defrosting less ice build up, faster defrosting
- 1 hyperFresh plus box with adjustable humidity keeps fruit and vegetables fresh for longer.
- Vario shelf useful storage when required
- Easy access shelf easy access and everything in sight
- touch control enduring elegance pefectly under control

Country Specific Options

• Based on the results of the standard 24-hour test. Actual

consumption depends on usage/position of the appliance.

Design features

Dimension and installation


Additional features


Performance and Consumption

• EU19_EEK_D: E


- Total Volume : 272 |
- Net Fridge Volume : 209 l
- Net Freezer Volume : 63 l
- Freezing capacity 24h : 5 kg
- Annual Energy Consumption: 207 kWh/a
- Climate Class: SN-ST
- Noise Level : 36 dB , EU19_Noise emission class_D: C
- Temperature rise time : EU19_Temperature rise time_D: 12 H

iQ500, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, flat hinge KI87SAFE0G





The specified unit door dimensions are valid for a door gap of 4 mm. measurements in mm measurements in mm Recommended gap dimensions for flat hinges



The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.