

## Series 6, Built-in fridge, 177.5 x 56 cm, soft close flat hinge KIR81ADD0G











 $3 \times egg tray$ ,  $1 \times Heavy-duty hinge support$ 

KSZGGM00 Butter box

# The spacious built-in fridge with VitaFresh XXL drawer for fruit and vegetables and high stability door trays provides optimal food storage.

- VitaFresh XXL <0°C>: keeps food fresh for longer in extra-large climate-controlled fridge drawers.
- LED lighting: all your items in perfect view.

A ↑ G

- Super Cool function: cools new food faster, to protect what is already inside.
- MultiBox XXL: extra-large drawer for your fruit and vegetables.

Energy Efficiency Class:
Average annual energy consumption in kilowatt hour per year
(kWh/a):
Sum of volume of frozen compartments:
Sum of volume of chill compartments:
Airborne acoustical noise emissions :
Airborne acoustical noise emissions:
Built-in / Free-standing:
Door panel options:
Height:
Width of the appliance:
Depth:
Min. required niche size for installation (HxWxD): 1775.0 x 560 x 550
mm
Net weight:
Fuse protection:
Door hinge:
Voltage:
Frequency: 50 Hz
Length electrical supply cord:
Number of compressors:1
Number of independent cooling systems:1
Interior ventilator:
Reversible Door Hinge:
Number of Adjustable Shelves in fridge compartment: 4
Shelves for Bottles:
EAN code:
Brand:
Product name / Commercial code:KIR81ADD0G
Product category:Refrigerator
Frost free system:No
Installation typology: Integrated
Included accessories:3 x egg tray, 1 x Heavy-duty hinge support





### Series 6, Built-in fridge, 177.5 x 56 cm, soft close flat hinge KIR81ADD0G

## The spacious built-in fridge with VitaFresh XXL drawer for fruit and vegetables and high stability door trays provides optimal food storage.

- Built-in fridge
- Fixed hinge, SoftClosing Door dampens door movement, for smooth and effortless closure

#### **Performance and Consumption**

- EU19\_EEK\_D: D
- Total Volume : 310 l
- Annual Energy Consumption: 91 kWh/a
- Climate Class: SN-ST
- Noise Level: 34 dB, EU19\_Noise emission class\_D: B

#### **Functions**

- Bright interior LED fridge light

#### Design features

- LED electronic control
- Optical and accoustical
- Super Cooling: automatic deactivation
- Automatic defrost fridge
- Easy clean interior

#### **Design features**

- Net Fridge Volume : 310 l
- 7 safety glass shelves in fridge compartment of which 4 are height adjustable
- 5 door bins
- Metal bottle rack

#### Freshness System

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer
- 1 MultiBox Transparent drawer with a rippled bottom, ideal for storing fruits and vegetables.

#### Key features - Fridge section

- Right hinged door, door reversible
- built-in, partly integrated
- Length of power cord:230 cm
- 220 240 V

#### Dimension and installation

- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D
- Dimensions: 177.2 cm H x 55.8 cm W x 54.8 cm D

#### **Key features - Freezer section**

- KIR81ADD0G


#### **Country Specific Options**


- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

#### **Additional features**



#### Series 6, Built-in fridge, 177.5 x 56 cm, soft close flat hinge KIR81ADD0G







#### Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges Å Weight A: Appliance door height including hinges in mm

- B: Undamped hinge, unit front in kg
- C: Damped hinge, unit front in kg
- D: Additional possible load in kg with heavy load kit

	Α	В	C	D
	1500-1750	22	22	
	720-1400	19	19	B+5 / C+5
	A1	15	19	B+5/C+5
	A2	15	19	






measurements in mm

### Air outlet min. 200 cm<sup>2</sup> max. min. 2200 560 560 recommended min. 550 1772<sup>+8</sup> Ventilation space in the base min. 200 cm<sup>2</sup> measurements in mm

measurements in mm Recommended gap dimensions for flat hinges



The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.