

iQ300, Wall-mounted cooker hood, 60 cm, Stainless steel LC67QFM50B



B



Pyramid design extractor hood with a high extraction rate.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ touchControl: quickly and easily manage the power levels and the LED light

Features

Technical Data

Typology : Wall-mounted
 Length of electrical supply cord : 130 cm
 Height of the chimney : 582-912/582-1022 mm
 Height of product, without chimney : 94 mm
 Minimum distance above an electric hob : 550 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 11.6 kg
 Type of control : Electronic
 Maximum output air extraction : 446 m³/h
 Boost position output recirculating : 499 m³/h
 Maximum output recirculating air : 404 m³/h
 Boost position air extraction : 747 m³/h
 Number of lights (Stck) : 2
 Noise level : 65 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable stainless steel
 EAN code : 4242003811146
 Connection rating : 255 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Wall-mounted

Optional accessories

LZ50661	Backboard 60 x 72 cm
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ11FXD51	Long Life recirculation kit external
LZ11FXC56	Clean Air Plus recirc. kit external
LZ11DXI16	Clean Air Plus recirculation kit
LZ11DXI14	Clean Air Standard recirculation kit
LZ10FXJ00	Long Life recirculation kit
LZ10DXA00	Standard odor filter (replacement)



iQ300, Wall-mounted cooker hood, 60 cm, Stainless steel LC67QFM50B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 445 m³/h
- Intensive 747 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 65 dB dB*

Features

- touchControl for extractor speeds and light
- touchControl with Electronic display
- 3 x power levels plus intensive setting
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 x metal grease filter cassettes
- Steel filter cover
- Installation: wall

Design

- Chimney hood
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 747 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 65 dB(A) re 1 pW
- Intensive: 73 dB(A) re 1 pW
- Power rating: 255 W
- Light Intensity: 242 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 676-1006 x 600 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 676-1116 x 600 x 500mm
-
- Dimensions recirculating with CleanAir module (HxWxD):
- 744 x 600 x 500mm - mounting with outer chimney
- 874-1204 x 600 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 61 kWh/year*

Optional accessories

- Recirculating kit LZ11FXD51

* In accordance with the EU-Regulation No 65/2014

iQ300, Wall-mounted cooker hood, 60 cm, Stainless steel
LC67QFM50B

Dimensioned drawings

