

# iQ700, Wall-mounted cooker hood, 90 cm, clear glass black printed LC91KWW62S



## Optional accessories

HZG9AS00S	Adapter
LZ10AKR00	Long Life recirculation kit (chimless)
LZ10AKS00	Long Life recirculation kit
LZ11AKB16	Clean Air Plus odor filter (replacement)
LZ11AKI16	Clean Air Plus recirculation kit
LZ11AKV16	Clean Air Plus recirc. kit (chimless)

A+

Angled extractor hood with outstanding design and high extraction rate for a powerful performance.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ cookConnect and climateControl sensor: detects and removes steam and odours automatically
- ✓ emotionLight Pro: Adapt your extractor hood to your style.
- ✓ voiceControl – Control hood functions and lighting using your voice.
- ✓ Home Connect – The app that makes your hood work smarter.

## Features

### Technical Data

Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the appliance:	323 mm
Minimum distance above an electric hob:	450 mm
Minimum distance above a gas hob:	650 mm
Weight:	24.8 kg
Control panel:	Electronic
Number of speed settings:	3-stage + 2 intensive
Maximum output air extraction:	527 m³/h
Boost position output recirculating:	781.0 m³/h
Maximum output recirculating air:	497 m³/h
Boost position air extraction:	988 m³/h
Maximum Air flow:	527 m³/h
Number of lights:	2
Noise level:	56 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Other
EAN code:	4242003909416
Connection Rating:	270 W
Fuse protection:	10 A
Nominal power:	220-240 V
Frequency:	50; 60 Hz
Plug type:	Gardy plug w/ earthing
Installation type:	Wall-mounted
Delay Shut off modes:	10 min



iQ700, Wall-mounted cooker  
hood, 90 cm, clear glass black  
printed  
**LC91KWW62S**

Features

**Key performance features:**

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Noise max. Normal Level: Noise, max. speed in normal us: 56 dB dB\*

**Home Connect: Remote Monitoring and Control**

- Home Connect: Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Adjustable color temperature (2.700 K - 5.000 K) for adaption to the room lighting available via Home Connect

**Special features**

- climateControl sensor
- cookConnect hob based hood control
- Additional functions: Ambient light RGB
- Additional noise reduction insulation
- Boost function
- Main On / Off switch, cookConnect hob based hood control, Smart Device, None
- Additional functions: Ambient light RGB
- 3 power levels and 2 intensive settings
- touchControl
- softLight with dimmer function
- 2 x LM5-04\_LED\_3W
- Efficient BLDC motor
- Gas spring 3
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- Grease and charcoal filter saturation indicators
- 2 x metal grease filter cassettes
- Black grease filter

**Design**

- 90 cm
- Chimney hood
- Installation: wall
- Black glass
- Equipped with black chimney section
- 2 capture areas: front side and bottom side
- Rim ventilation
- easy to clean Inner frame

**Performance/technical information**

- Suitable for ducted and re-circulating operation
- In recirculation operation chimless use possible
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 527 m<sup>3</sup>/h
  - Intensive 988 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 56 dB(A) re 1 pW
  - Intensive: 69 dB(A) re 1 pW

- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 497 m<sup>3</sup>/h
- Intensive: 781 m<sup>3</sup>/h
- Noise level in recirculation mode with Clean Air Plus odor filter : Max. normal use: 68 dB(A) re 1 pW
- Intensive: 79 dB(A) re 1 pW
- Installation system: Wall fixing inclined/flat/cube
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 930-1200 x 890 x 499 mm
- Dimensions recirculating, chimney (HxWxD): 990-1260 x 890 x 499mm
- Dimensions recirculating, chimless (HxWxD): 454 mm x 890 x 499mm
- Power rating: 270 W
- Light Intensity: 348 lux
- Average Energy Consumption: 39.3 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*

\* In accordance with the EU-Regulation No 65/2014

iQ700, Wall-mounted cooker  
hood, 90 cm, clear glass black  
printed  
LC91KWW62S

Dimensioned drawings

