

## iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B



Box design extractor hood with high extraction rate.

✓ LED lights: for optimal visibility and ambience while cooking.

### Features

#### Technical Data

Typology : Wall-mounted  
 Approval certificates : CE, E17D UKCA marking, G-Mark, VDE  
 Length of electrical supply cord : 130 cm  
 Height of the chimney : 583-912/583-1022 mm  
 Height of product, without chimney : 53 mm  
 Minimum distance above an electric hob : 550 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 12.8 kg  
 Type of control : mechanical  
 Number of speed settings : 3  
 Maximum output air extraction : 365 m<sup>3</sup>/h  
 Maximum output recirculating air : 240 m<sup>3</sup>/h  
 Number of lights (Stck) : 2  
 Noise level : 64 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242003811184  
 Connection rating : 100 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : GB plug  
 Installation type : Wall-mounted



### Optional accessories

LZ50961	Backboard 90 x 72 cm
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ11FXD51	Long Life recirculation kit external
LZ11FXC56	Clean Air Plus recirc. kit external
LZ11DXI16	Clean Air Plus recirculation kit
LZ11DXI14	Clean Air Standard recirculation kit
LZ10FXJ00	Long Life recirculation kit
LZ10DXU00	Standard recirculation kit
LZ10DXA00	Standard odor filter (replacement)

## iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B

### Features

#### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB\*

#### Features

- Push button control for extractor speeds and light
- 3 x power levels
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- 3 x metal grease filter cassettes - dishwasher safe
- Installation: wall

#### Design

- Chimney hood
- Mechanical

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Maximum extraction rate exhaust air 365 m<sup>3</sup>/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Power rating: 100 W
- Light Intensity: 91 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 635-1075 x 900 x 500mm
- 
- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 900 x 500mm - mounting with outer chimney
- 833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*
- Average Energy Consumption: 53.1 kWh/year\*

#### Optional accessories

- Recirculating kit LZ00XXP00

\* In accordance with the EU-Regulation No 65/2014

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel  
LC94BBC50B

Dimensioned drawings

