

## iQ300, Wall-mounted cooker hood, 90 cm, clear glass LC97AFM50B



**B**



Glass design extractor hood with a high extraction rate.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ touchControl: quickly and easily manage the power levels and the LED light

### Features

#### Technical Data

Typology : Wall-mounted  
 Length of electrical supply cord : 130 cm  
 Height of the chimney : 576-897/576-1007 mm  
 Height of the appliance : 50 mm  
 Minimum distance above an electric hob : 550 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 16.0 kg  
 Type of control : Electronic  
 Maximum output air extraction : 464 m<sup>3</sup>/h  
 Boost position output recirculating : 499 m<sup>3</sup>/h  
 Maximum output recirculating air : 404 m<sup>3</sup>/h  
 Boost position air extraction : 702 m<sup>3</sup>/h  
 Number of lights (Stck) : 2  
 Noise level : 67 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable stainless steel  
 EAN code : 4242003811245  
 Connection rating : 255 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : GB plug  
 Installation type : Wall-mounted

### Optional accessories

LZ50961	Backboard 90 x 72 cm
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ11FXD51	Long Life recirculation kit external
LZ11FXC56	Clean Air Plus recirc. kit external
LZ11DXI16	Clean Air Plus recirculation kit
LZ11DXI14	Clean Air Standard recirculation kit
LZ10FXJ00	Long Life recirculation kit
LZ10DXA00	Standard odor filter (replacement)



## iQ300, Wall-mounted cooker hood, 90 cm, clear glass LC97AFM50B

### Features

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 463 m<sup>3</sup>/h
- Intensive 702 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 67 dB dB\*

#### Features

- touchControl for extractor speeds and light
- touchControl with Electronic display
- 3 x power levels plus intensive setting
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 1 x metal grease filter cassette
- Steel filter cover
- Installation: wall

#### Design

- Chimney hood
- Electronic control

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 702 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 67 dB(A) re 1 pW
- Intensive: 74 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 404 m<sup>3</sup>/h
- Intensive: 499 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 72 dB(A) re 1 pW
- Intensive: 76 dB(A) re 1 pW
- Power rating: 255 W
- Light Intensity: 232 lux
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 617-947 x 900 x 488 mm
- Dimensions recirculating, chimney (HxWxD): 617-1057 x 900 x 488 mm
- 
- Dimensions recirculating with CleanAir module (HxWxD):
- 686 x 900 x 488 mm - mounting with outer chimney
- 815-1145 x 900 x 488 mm - mounting with telescopic chimney
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 58 kWh/year\*

#### Optional accessories

- Recirculating kit LZ12250

\* In accordance with the EU-Regulation No 65/2014

iQ300, Wall-mounted cooker hood, 90 cm, clear glass  
LC97AFM50B

Dimensioned drawings

