

iQ700 LC98KC652B



A

Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 730 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-920/582-1030
 Height of product, without chimney (mm) : 387
 Minimum distance above an electric hob : 400
 Minimum distance above a gas hob : 500
 Net weight (kg) : 24.109
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 410
 Boost position output recirculating (m³/h) : 380
 Maximum output recirculating air (m³/h) : 310
 Boost position air extraction (m³/h) : 730
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 58
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 EAN code : 4242003651414
 Connection rating (W) : 166
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Wall-mounted

Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53251	Active carbon filter
LZ53250	Recirculating kit
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ00XXP00	CleanAir act.carbon filter regenerative



iQ700

LC98KC652B

Features

Design

- 90 cm wide
- Soft touch button control for extractor speeds and light
- White electronic display
- Blue indicator lights
- Black glass canopy
- Height adjustable chimney sections
- For wall mounted installation

Key Information

- Electronic control
- Electronic power level display
- climateControl Sensor
- LED lights
- softLight with dimmer function
- 2 x metal grease filter cassettes
- Steel filter cover
- Soft touch button control with 7-segment display
- Boost function
- Grease and charcoal filter saturation indicators

Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 410 m³/h
 - Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic intensive revert

Optional accessories

- Re-circulating kit - LZ53250

iQ700 LC98KC652B

Dimensioned drawings

