

## iQ100, Integrated cooker hood, 60 cm, silver LE63MAC00B



This fold-out integrated hood with a high extraction rate for powerful performance is hidden in the upper cabinet unit.

✓ LED lights: for optimal visibility and ambience while cooking.

### Features

#### Technical Data

Typology : Built-in/Built-under  
 Approval certificates : CE  
 Length of electrical supply cord : 150 cm  
 Minimum distance above an electric hob : 500 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 11.4 kg  
 Type of control : mechanical  
 Number of speed settings : 3  
 Maximum output air extraction : 368 m<sup>3</sup>/h  
 Maximum output recirculating air : 272 m<sup>3</sup>/h  
 Number of lights (Stck) : 2  
 Noise level : 62 dB(A) re 1 pW  
 Diameter of air outlet : 150 / 120 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242003806487  
 Connection rating : 126 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : GB plug  
 Installation type : Wall-mounted



### Optional accessories

LZ10IMA00 Standard odor filter

## iQ100, Integrated cooker hood, 60 cm, silver LE63MAC00B

### Features

#### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 368 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB\*

#### Features

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- Colour Temperature: 2700 K
- 2 x metal grease filter cassettes
- Installation: Between Cupboards

#### Design

- Integrated hood
- Mechanical

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Power rating: 126 W
- Light Intensity: 188 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating, chimney (HxWxD): 402-402 x 599 x 271 mm
- 
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 65.7 kWh/year\*

#### Optional accessories

- Recirculating kit LZ10IMA00

\* In accordance with the EU-Regulation No 65/2014

iQ100, Integrated cooker hood, 60 cm,  
silver  
LE63MAC00B

Dimensioned drawings

