

**iQ100, Integrated cooker hood,
60 cm, Silver
LE66MAC00B**



LZ10IMA00 Standard odor filter

This fold-out integrated hood with a high extraction rate for powerful performance is hidden in the upper cabinet unit.

✓ Illuminate your cooking space with LED lights for optimal visibility and ambience setting.

Technical specifications

Typology:	Built-in/Built-under
Length electrical supply cord:	150.0 cm
Height of the appliance:	402 mm
Minimum distance above an electric hob:	500 mm
Minimum distance above a gas hob:	650 mm
Weight:	10.7 kg
Control panel:	mechanical
Number of speed settings:	3
Maximum output air extraction:	625 m³/h
Maximum output recirculating air:	416 m³/h
Maximum Air flow:	625 m³/h
Number of lights:	2
Noise level:	70 dB(A) re 1pW
Diameter of air outlet:	150 / 120 mm
Grease filter material:	Washable aluminium
EAN code:	4242003806500
Connection Rating:	256 W
Fuse protection:	10 A
Nominal power:	220-240 V
Frequency:	50; 60 Hz
Plug type:	GB plug
Installation type:	Wall-mounted



iQ100, Integrated cooker hood, 60 cm, Silver LE66MAC00B

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 625 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- 2 x metal grease filter cassettes

Design

- Integrated hood
- Installation: Between Cupboards
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 68.4 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating, chimney (HxWxD): 402-402 x 599 x 271 mm

Optional accessories

- Recirculating kit LZ10IMA00

* In accordance with the EU-Regulation No 65/2014

iQ100, Integrated cooker hood,
60 cm, Silver
LE66MAC00B

