

iQ700, Island cooker hood, 90 cm, Stainless steel LF91BA582B

A



The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 710 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 49 dB the hood is extremely quiet when being used.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 698-878/698-998
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 32.527
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 570
 Boost position output recirculating (m³/h) : 500.0
 Boost position air extraction (m³/h) : 710
 Number of lights (Stck) : 4
 Noise level (dB(A) re 1 pW) : 63
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 EAN code : 4242003675373
 Connection rating (W) : 272
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation type : Island

Optional accessories

LZ57600	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ12530	Extension for mounting kit 1000 mm
LZ12510	Extension for mounting kit 500 mm
LZ12410	Adapter for roof inclination front/back
LZ12385	Chimney extension 1600 mm
LZ12310	Adapter for roof inclination left/right
LZ12285	Chimney extension 1100 mm
LZ00XP00	Long Life odor filter (replacement)



iQ700, Island cooker hood, 90 cm, Stainless steel LF91BA582B

Features

Design

- 90 cm wide
- Stainless Steel
- White electronic display
- Electronic control via touchControl
- For ceiling mounted installation
- Designed for suspended or flush ceiling installation

Key Information

- touchControl for extractor speeds and light
- climateControl Sensor
- Boost function
- 4 x LED lights
- 3 x metal grease filter cassettes - dishwasher safe
- Grease filter saturation indicator
- Steel filter cover, Steel filter cover
- Rim ventilation
- Inner frame

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 570 m³/h
 - Intensive 710 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 63 dB(A) re 1 pW (49 dB(A) re 20 µPa sound pressure)
 - Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Additional noise reduction insulation
- 3 power levels and 2 intensive settings
- Power rating: 272 W
- Automatic intensive revert
- Automatic after running (10 minutes)
- Noise max. Normal Level: 63 dB*
- Extractor hose 120 mm
- Dimensions (WxD): 900 x 600 mm
- Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm
- Dimensions recirculating with cleanAir module (HxWxD): 812-1044 x 900 x 600 mm
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Light Intensity: 888 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 39.6 kWh/year*
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: A*

* In accordance with the EU-Regulation No 65/2014

iQ700, Island cooker hood, 90 cm,
Stainless steel
LF91BA582B

Dimensioned drawings

