

## iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B



|           |  |
|-----------|--|
| LZ00XXP00 | Long Life odor filter (replacement)      |
| LZ12285   | Chimney extension 1100 mm                |
| LZ12310   | Adapter for roof inclination left/right  |
| LZ12385   | Chimney extension 1600 mm                |
| LZ12410   | Adapter for roof inclination front/back  |
| LZ12510   | Extension for mounting kit 500 mm        |
| LZ12530   | Extension for mounting kit 1000 mm       |
| LZ22CBI14 | Clean Air Standard recirculation kit     |
| LZ22CXC56 | Clean Air Plus recirc. kit external      |
| LZ22FXD51 | Long Life recirculation kit external     |
| LZ31XXB16 | Clean Air Plus odor filter (replacement) |
| LZ32CBB14 | Clean Air Standard odor filter (repl.)   |

The island hood features a very high extraction rate in a distinguished design that coordinates with a range of Siemens appliances, as well as your kitchen.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ cookConnect and climateControl sensor: detects and removes steam and odours automatically
- ✓ voiceControl – Control hood functions and lighting using your voice.
- ✓ Home Connect – The app that makes your hood work smarter.
- ✓ Peace of mind is just a click away - remoteMonitoring.

|   |       |                          |
|---|-------|--------------------------|
| Color chimney:                          | ..... | Stainless steel          |
| Typology:                               | ..... | Island/Ceiling           |
| Length electrical supply cord:          | ..... | 130.0 cm                 |
| Height of the chimney:                  | ..... | 698-878/698-998 mm       |
| Height of the appliance:                | ..... | 46 mm                    |
| Minimum distance above an electric hob: | ..... | 550 mm                   |
| Minimum distance above a gas hob:       | ..... | 650 mm                   |
| Weight:                                 | ..... | 29.9 kg                  |
| Control panel:                          | ..... | Electronic               |
| Number of speed settings:               | ..... | 3-stage + 2 intensive    |
| Maximum output air extraction:          | ..... | 598 m³/h                 |
| Boost position output recirculating:    | ..... | 561 m³/h                 |
| Maximum output recirculating air:       | ..... | 462 m³/h                 |
| Boost position air extraction:          | ..... | 981 m³/h                 |
| Maximum Air flow:                       | ..... | 598 m³/h                 |
| Number of lights:                       | ..... | 4                        |
| Noise level:                            | ..... | 62 dB(A) re 1pW          |
| Diameter of air outlet:                 | ..... | 120 / 150 mm             |
| Grease filter material:                 | ..... | Washable stainless steel |
| EAN code:                               | ..... | 4242003832073            |
| Connection Rating:                      | ..... | 266 W                    |
| Fuse protection:                        | ..... | 10 A                     |
| Nominal power:                          | ..... | 220-240 V                |
| Frequency:                              | ..... | 50; 60 Hz                |
| Plug type:                              | ..... | GB plug                  |
| Installation type:                      | ..... | Island                   |



## iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B

### Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 598 m<sup>3</sup>/h
  - Intensive 981 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB\*

### Home Connect: Remote Monitoring and Control

- Home Connect: Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Interval function: available via Home Connect
- Silence function: available via Home Connect

### Features

- touchControl with 7-segment display
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- cookConnect hob based hood control
- climateControl sensor
- Fully automatic hood
- softLight with dimmer function
- 4 x 1.5W LED
- Additional noise reduction insulation
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (Automatic after running (10 minutes))
- Grease and charcoal filter saturation indicators
- 3 x metal grease filter cassettes - dishwasher safe
- Steel filter cover

### Design

- Stainless Steel
- Installation: Ceiling
- Electronic control

### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 981 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 62 dB(A) re 1 pW
  - Intensive: 73 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:

- Extraction rate in recirculation mode: Max. normal use: 462 m<sup>3</sup>/h
- Intensive: 561 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 68 dB(A) re 1 pW
- Intensive: 72 dB(A) re 1 pW
- Power rating: 266 W
- Light Intensity: 411 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating, chimney (HxWxD): 744-1044 x 898 x 600mm
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 37.5 kWh/year\*

### Optional accessories

- Recirculating kit LZ31XXB16

\* In accordance with the EU-Regulation No 65/2014

**iQ700, Island cooker hood, 90 cm,  
Stainless steel  
LF91BUV50B**

