

**iQ300, Telescopic cooker hood, 90 cm, Silver metallic  
LI94MA531B**



LZ11ITB14	Clean Air Standard odor filter (repl.)
LZ11ITI14	Clean Air Standard recirculation kit
LZ49521	Handle strip white
LZ49561	Handle strip black
LZ49850	Handle strip

For clean lines the powerful telescopic cooker hood disappears into an upper cabinet, perfect for modern kitchens.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Illuminate your cooking space with LED lights for optimal visibility and ambience setting.

Typology:	..... Pull-out
Length electrical supply cord:	..... 175.0 cm
Required niche size for installation (HxWxD):	..... 162mm x 526.0mm x 290mm mm
Height of the appliance:	..... 203 mm
Minimum distance above an electric hob:	..... 430 mm
Minimum distance above a gas hob:	..... 650 mm
Weight:	..... 10.4 kg
Control panel:	..... Electronic
Number of speed settings:	..... 3-stages + intensive setting
Maximum output air extraction:	..... 266 m³/h
Boost position output recirculating:	..... 353 m³/h
Maximum output recirculating air:	..... 263 m³/h
Boost position air extraction:	..... 412 m³/h
Maximum Air flow:	..... 266 m³/h
Number of lights:	..... 3
Noise level:	..... 63 dB(A) re 1pW
Diameter of air outlet:	..... 120 / 150 mm
Grease filter material:	..... Washable aluminium
EAN code:	..... 4242003880234
Connection Rating:	..... 76 W
Fuse protection:	..... 10 A
Nominal power:	..... 220-240 V
Frequency:	..... 50; 60 Hz
Plug type:	..... GB plug
Installation type:	..... Built-in



## iQ300, Telescopic cooker hood, 90 cm, Silver metallic LI94MA531B

### Features

- Soft touch button control with Electronic display
- 3 x power levels plus intensive setting
- 3 x 1,5W LED
- Efficient BLDC motor
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 minutes))
- 3 x metal grease filter cassettes - dishwasher safe

### Design

- 90 cm wide
- Silver metallic lacquer
- Handle strip specification: stainless steel with logo
- Filter cover stainless steel, perforated and dishwasher safe

### Performance

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit (accessory) needed
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 266 m<sup>3</sup>/h
- Intensive: 412 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 63 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 63 dB(A) re 1 pW
- Intensive: 70 dB(A) re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 355 lux
- Power rating: 76 W
- Average Energy Consumption: 22.2 kWh/year\*
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*

### Planning and installation information

- Dimensions (HxWxD): 203 x 898 x 290 mm
- Built-in dimensions (HxWxD): 162 x 526 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

\* In accordance with the EU-Regulation No 65/2014

**iQ300, Telescopic cooker hood, 90 cm, Silver metallic  
LI94MA531B**



