

For clean lines the powerful telescopic cooker hood disappears into an upper cabinet, perfect for modern kitchens.

- ✓ iQdrive motor The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Extremely quiet The quiet hood that keeps the calm your kitchen.











Intional accessories

LZ49560	Handle strip black
LZ49200	Installation kit for 90cm wide wall unit
LZ45650	Standard recirculation kit
LZ45610	Standard odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
I 711ITD11	Long Life recirculation kit external

Feature

Technical Data

Typology: Pull-out

Approval certificates : CE, VDE

Length of electrical supply cord: 175 cm

Required niche size for installation (HxWxD) : 385mm x 524.0mm x

290mm mm

Minimum distance above an electric hob : 430 mm Minimum distance above a gas hob : 650 mm

Net weight: 14.055 kg Type of control: Electronic

Number of speed settings : 3-stage + 2 intensive Maximum output air extraction : 395 m³/h Boost position output recirculating : 628 m³/h Maximum output recirculating air : 358 m³/h Boost position air extraction : 708 m³/h

Number of lights (Stck): 2 Noise level: 56 dB(A) re 1 pW Diameter of air outlet: 150 / 120 mm

Grease filter material : Washable stainless steel

EAN code: 4242003745755 Connection rating: 146 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 60; 50 Hz Plug type: GB plug Installation type: Built-in





Feature:

Key Information

- Soft touch button control with 7-segment display
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Silence kit
- 2 x LED lights
- softLight with dimmer function
- · Neutral white lights
- Efficient BLDC motor
- Automatic after running (Automatic after running (10 minutes))
- 3 x metal grease filter cassettes dishwasher safe
- Grease and charcoal filter saturation indicators
- Steel filter cover

Design

- 90 cm Extractor hood with telescopic canopy
- $\bullet \ Installation \ system: Telescopic \ comfort \ installat.$
- Stainless Steel
- Electronic control via Soft touch button control
- Blue indicator lights

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- \bullet Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 394 m³/h
- Intensive 708 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 56 dB(A) re 1 pW
- Intensive: 68 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 358 m³/h
- Intensive: 628 m³/h
- Noise level in recirculation mode:
- Max. normal use: 60 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- Additional noise reduction insulation
- Power rating: 146 W
- Light Intensity: 601 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 37.9 kWh/year*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Built-in dimensions (HxWxD): 385 x 524 x 290 mm
- Dimensions exhaust air (HxWxD): 426-426 x 898 x 290 mm
- * In accordance with the EU-Regulation No 65/2014







