

iQ700, Ceiling cooker hood, 90 cm, White LR99CQS25B

A



The studioLine ceiling hood takes performance to new heights, with its extremely high extraction rate and sleek design.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ cookConnect and climateControl sensor: detects and removes steam and odours automatically
- ✓ voiceControl – Control hood functions and lighting using your voice.
- ✓ Home Connect – The app that makes your hood work smarter.
- ✓ Peace of mind is just a click away - remoteMonitoring.

Features

Technical Data

Typology : Island/Ceiling
 Approval certificates : CE, E17D UKCA marking, VDE
 Length of electrical supply cord : 130 cm
 Required niche size for installation (HxWxD) : 299mm x 888.0mm x 487mm mm
 Minimum distance above an electric hob : 650 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 29.6 kg
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction : 459 m³/h
 Boost position output recirculating : 637.0 m³/h
 Maximum output recirculating air : 419 m³/h
 Boost position air extraction : 933 m³/h
 Number of lights (Stck) : 1
 Noise level : 56 dB(A) re 1 pW
 Diameter of air outlet : 150 mm
 Grease filter material : Other
 EAN code : 4242003834053
 Connection rating : 276 W
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Island

Optional accessories

LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ21JCC56	Clean Air Plus recirc. kit external inox
LZ21JCC26	Clean Air Plus recirc.kit external white
LZ20JCD50	Long Life recirc. kit external inox
LZ20JCD20	Long Life recirc. kit external white



iQ700, Ceiling cooker hood, 90 cm, White LR99CQS25B

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 458 m³/h
- Intensive: 933 m³/h
- Noise max. Normal Level: Noise, max. speed in normal use: 56 dB dB*

Home Connect: Remote Monitoring and Control

- Home Connect: Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Adjustable color temperature (2.700 K - 5.000 K) for adaption to the room lighting available via Home Connect
- Interval function: available via Home Connect
- Silence function: available via Home Connect

Features

- climateControl sensor
- cookConnect hob based hood control
- Fully automatic hood
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- softLight with dimmer function
- Interval operation
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (Automatic after running (10 minutes))
- Grease and charcoal filter saturation indicators
- 2 x metal grease filter cassettes
- Glass filter cover, Steel filter cover
- Black grease filter with stainless steel frame
- Infrared remote control
- Rim ventilation
- Easy to clean inner frame

Design

- White
- Installation: Ceiling
- Rotatable motor: possible to position the air outlet on all four sides
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 933 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 56 dB(A) re 1 pW
- Intensive: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:

- Extraction rate in recirculation mode: Max. normal use: 419 m³/h
- Intensive: 637 m³/h
- Noise level in recirculation mode with Clean Air Plus odor filter : Max. normal use: 63 dB(A) re 1 pW
- Intensive: 72 dB(A) re 1 pW
-
- Power rating: 276 W
- Light Intensity: 439 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 315-315 x 900 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 315-315 x 900 x 500 mm
-
- Blower Efficiency Class: A*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: E*
- Average Energy Consumption: 47.6 kWh/year*

Optional accessories


- Recirculating kit LZ00XXP00

* In accordance with the EU-Regulation No 65/2014


iQ700, Ceiling cooker hood, 90 cm,
White
LR99CQS25B

Dimensioned drawings

The fan outlet can be turned in all four directions




measurements in mm



Never fit directly onto plasterboard or similar lightweight construction materials of the suspended ceiling. A suitable substructure is required that is securely fixed to the concrete ceiling.


measurements in mm

measurements in mm
Air extraction




A: Optimum performance 700-1500
B: From upper edge of pan support

measurements in mm
Air recirculation



A: Optimum performance 700-1500
B: From upper edge of pan support

measurements in mm
Air recirculation



A: Optimum performance 700-1500
B: From upper edge of pan support