

Series 6, Gas hob, 90 cm, Stainless steel PCR9A5B90





HEZ211310 Simmer cap HEZ298105 Simmer plate HEZ298107 Wok ring

HEZ298115 Small pot support

The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- Dual Control Wok enables you to precisely control flame level by
- \bullet different flame rings on the same burner.
- Dual ring burner has a wide range of power from a high heat dual flame down to one small simmer flame.
- Five powerful high-efficiency gas burners allows you to cook multiple dishes with a full range BTU performance.

Appliance type: gas ho	b w integrated controls
Built-in / Free-standing:	Built-in
Heating type:	Gas
Number of cooking zones:	5
Type of control setting devices:	sword knobs
Min. required niche size for installation (HxW)	(D):45 x 850-852 x
490-502 mm	
Width of the appliance:	915 mm
Dimensions:	53x915x520 mm
Dimensions of the packed product (HxWxD): .	165 x 1116 x 659 mm
Net weight:	15.5 kg
Gross weight:	17.7 kg
Residual heat indicator:	without
Location of control panel:	Front
Basic surface material:	Stainless steel
Color of surface:	Stainless steel
Length electrical supply cord:	150.0 cm
EAN code:	4242002802787
Gas connection rating:	12500 W
Fuse protection:	3 A
Voltage:	220-240 V
Frequency:	50; 60 Hz





Series 6, Gas hob, 90 cm, Stainless steel PCR9A5B90

The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 gas burners:
- Including 1 dual control wok burner: use an extra wide power range, separately controlling two flame rings.
- Left front: economy burner up to 1 kW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 5 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: standard burner up to 1.75 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 915 x 520
- Required niche size for installation (HxWxD mm) : $45 \times 850 \times (490 502)$
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 12.5 KW



Series 6, Gas hob, 90 cm, Stainless steel PCR9A5B90

