


*N 50, GAS HOB, 60 CM, STAINLESS STEEL
T26GKH8N0*



Z1365WX0	Wireless food thermometer
Z2402X0	Small pot support
Z2471X0	Wok ring
Z2480X0	Simmer plate
Z9404SE0	4 pieces Set
Z9406SE0	6 pieces Set

The gas hob with pan supports that are suitable for dishwashers - for easy cleaning.

- ✓ Sword Dials: For easy, enjoyable control while cooking.
- ✓ Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- ✓ Wok Burner: Powerful cooking at up to 3.3 kW.
- ✓ Gas Safety Cut-Off: Safety first! No flame, no gas flow.
- ✓ Biomethane Ready: Power your hob with renewable biomethane gas.

Product name/family:gas hob w
integrated controls
Built-in / Free-standing: Built-in
Energy input: Gas
Number of cooking zones: 4
Type of control setting devices: sword knobs
Required niche size for installation (HxWxD): 45 x 560-560 x
480-490 mm
Width of the appliance: 582 mm
Dimensions: 51.1x582x520 mm
Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm
Net weight: 9.9 kg
Gross weight: 10.9 kg
Residual heat indicator: Separate
Location of control panel: Front
Basic surface material: Stainless steel
Color of surface: Stainless steel
Length electrical supply cord: 100.0 cm
EAN code: 4242004284574
Gas connection rating: 7800 W
Fuse protection: 3 A
Voltage: 220-240 V
Frequency: 50; 60 Hz



N 50, GAS HOB, 60 CM, STAINLESS STEEL T26GKH8N0

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Cleaning

- Dishwasher suitable pan supports for easy cleaning.

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar
- Liquid gas G30,31 28-30/37mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.1 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 7.8 KW

