

# iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC91BUR50B





### Optional accessories

LZ32CBB14 Clean Air Standard odor filter (repl.)
LZ12CBI14 Clean Air Standard recirculation kit
LZ10FXJ05 Long Life recirculation kit

The wall hood convinces with a very high extraction rate in a distinguished design that perfectly matches your kitchen.

- ✓ Powerful and quiet steam extraction iQdrive motor
- ✓ The boost setting temporarily increases the extraction rate to the highest when kitchen vapour is especially intense.
- ✓ Peak performance when steam escapes, and an automatic revert after a few minutes.
- ✓ Home Connect The app that makes your hood work smarter.
- ✓ Home Connect Smart appliances management. Anywhere. Anytime.

#### Feature

### **Technical data**

Typology: Wall-mounted

Height of the chimney : 582-908/568-1018 mm Height of product, without chimney : 46 mm

Net weight : 19.3 kg Type of control : Electronic

Number of speed settings: 3-stage + 2 intensive Maximum output air extraction: 602 m³/h Boost position output recirculating: 561 m³/h Maximum output recirculating air: 462 m³/h Boost position air extraction: 965 m³/h

Number of lights: 3

Noise level: 64 dB(A) re 1 pW Diameter of air outlet: 120 / 150 mm

Grease filter material: Washable stainless steel

Odour filter: No

Operating Mode: Exhaust or re-circulate air operation

Delay Shut off modes : 10 min

Optional accessories : LZ00XXP00, LZ10FXJ05, LZ11CXI16, LZ12265, LZ50960, LZ50961, LZ53450, LZ53451, LZ12FXD51, LZ31XXB16,

LZ32CBB14, LZ12CXC56, LZ12365, LZ12CBI14

Type of lamps used: LED Grease filter type: Kassette Connection Rating: 265 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50; 60 Hz Plug type: GB plug

Installation typology : Wall-mounted Material body : Stainless steel

Plug type : GB plug

Dimensions of the product, with chimney (if exists) (in) :  $I \times X$  Dimensions of the packed product : 23.03 x 25.59 x 38.18

Net weight: 42.000 lbs Gross weight: 56.000 lbs

Motor location: Integrated motor in hood chimney

No-return airflow flap : Yes

Dimensions of the product, with chimney (if exists) :  $614-1064 \times 898.0$ 

x 500.0 mm

Dimensions of the packed product (HxWxD) : 585 x 650 x 970 mm

Net weight : 19.3 kg Gross weight : 25.5 kg





# iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC91BUR50B

#### Feature

#### Design:

- Wall mounted chimney hood
- 90 cm wide
- Appliance colour: stainless steel
- Suitable for exhaust or re-circulated extraction

#### Feature

- BLDC for Ventilation Motor
- touchControl
- Extraction rate exhaust air according to EN 61591: 965 m³/h
- 3-stage + 2 intensive ventilation power settings
- Saturation indicator for metal grease filter
- 3 x 1,5W LED
- Dimmer light function
- softLight

### **Technical Information:**

- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Total connected load: 265 W

# **Supplied Accessories:**

- 3 dishwasher safe metal grease filters
- 150 mm diameter pipe (120 mm adapter enclosed)

## **Optional Accessory:**

- Charcoal Re-circulating kit
- cleanAir Recirculation kit



# iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC91BUR50B

# Dimensioned drawings measurements in mm ≥ 1204 614-954 (**A**) 614-1064 (**B**) 580 ≥ 120 (**A**) ≥ 10 (**B**) 448 \* from upper edge of pan support 394 min. 550 electric A: Air extraction B: Air recirculation C: Air outlet – slots for exhaust air to be mounted facing down recommendation 650 min. 650 gas\* measurements in mm dia. 120 dia. 150 424 379 438 max. 20 measurements in mm Exhaust-air outlet min. 6 min. 450 Socket 300 \* from upper edge of pan support min. 500 min. 550 electric recommendation 650 min. 650 gas\*

measurements in mm