### IQ700, Fully automatic espresso machine, Black CT718L1B0









TZ70003 1 x Brita Filter for EQ Coffee Machine TZ70033A 3 x Brita Filter for EQ Coffee Machine TZ80001A Cleaning tablets

TZ80001B 10 x Cleaning Tablets for EQ Coffee Mach

TZ80002A Descaling tablets

TZ80002B 3 x Descaling Tablets for EQ Coffee Mach

TZ80004A Care set espresso

TZ80004B Care Set for EQ Coffee Machines

Y988081012: Y988081300: Y988081302: Y988081303:

- ✓ TFT-Touchdisplay Pro Large colour touch display for comfortable operation.
- ✓ Siemens coffeeWorld, explore the huge variety of international coffee specialities with one swipe.
- ✓ Three different aroma profiles to choose from, according to your personal taste - aromaSelect.
- ✓ Save up to 30 individual coffee creations with Favorites.
- ✓ Fully automatic steam cleaning and optimal hygiene thanks to autoMilk Clean.

### **Technical Data**

Built-in / Free-standing:	Built-in
Frothing nozzle:	No
Display:	No
Water protection system:	
Portion sizes:	All cups
Dimensions:	.455 x 594 x 385 mm
Dimensions of the packed product (HxWxD):	540 x 478 x 670 mm
Min. required niche size for installation (HxWxI	D):449 x 558 x 376
mm	
EAN code:	4242003895580
Fuse protection:	10 A
Nominal power:	220-240 V
Frequency:	50/60 Hz
Plug type: G	ardy plug w/ earthing



# IQ700, Fully automatic espresso machine, Black CT718L1B0

### Features

### Flavour

- up to 29 different coffee specialties (within appliance and Home Connect app)
- warm milk, milk froth and hot water function
- aromaSelect 3 different aroma profiles (mild-balanced-distinctive)
- adjustable milk ratio for classic milk-mix beverages
- intelligent strength adjustment adaptive coffee management based on strength and size
- aromaDouble Shot less bitterness in large beverages due to two brewing processes

### Convenience

- TFT-Touchdisplay Pro 6.8" TFT- color display with touch and slide functionality
- Favorites: save up to 30 personalised beverages
- height adjustable bevarage outlet (up to 15 cm (max) high glasses )
- oneTouch DoubleCup get two cups at the touch of a button
- 2.4 I removable water tank

### Performance

- ceramDrive high-quality grinder made of wear-resistant ceramic
- water pump with 19 bar pressure

### Hygiene

- autoMilk Clean automatic steam cleaning after every drink
- calc'nClean combined descaling and cleaning program for less effort
- removable brewing unit for easy and hygienic cleaning
- dishwasher-proof: beverage outlet, drip tray and drip pans
- automatic reminder for cleaning, descaling or water filter change

### **Home Connect**

- remote control operate your appliance from everywhere
- coffeePlaylist select several drinks in the app, prepared in your chosen order
- additional coffee know-how
- software update always the newest software status
- online support
- Security: Security is of top priority at Home Connect. The Home Connect app has been tested and certified by TÜV IT. And the encrypted data transfer via Home Connect protocol protects against unauthorised access.
- integrated 0,7 I milk container
- 500 g bean container with aroma protection lid
- illuminated coffee outlet and stage
- adjustable grinding degree (multi-level)
- child lock

### Accessories

- included accessories: 1 x test strip
- Separately available accessories: cleaning tablets (TZ80001...), descaling tablets (TZ80002...), BRITA Intenza water filter (TZ70003/TZ70033), care set for fully-automatic espresso makers

(TZ80004...), adapter for milk carton (TZ70001), milk container (TZ90009)

# IQ700, Fully automatic espresso machine, Black CT718L1B0


### **Dimensioned drawings**

# Measurements in mm $\begin{array}{c|c} 6 & \longrightarrow & 19 \\ \hline & & & & & \\ \hline & & & & \\ \hline & & & & \\ \hline & & & & &$


**A:** 7.5 mm

### Measurements in mm

950-1450 mm




Bean and water containers are removed from the front Recommended installation height



Bean and water containers are removed from the front Recommended installation height 950–1450 mm

Measurements in mm

### Left corner installation



If using the  $92^{\circ}$  hinge limiter, the min. distance to the wall is only 100 mm

### Dimensioned drawings

