

**Serie | 2, canopy cooker hood, 53 cm  
DHL535BGB**



**Canopy cooker hoods are designed to be fully integrated for more flexibility when planning your kitchen.**

- An impressive extraction rate of 250 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.

**Technical Data**

Typology :	Traditional
Approval certificates :	CE, G-Mark, VDE
Length electrical supply cord (cm) :	130
Required niche size for installation (HxWxD) :	235mm x 500.0mm x 260mm
Minimum distance above an electric hob :	650
Minimum distance above a gas hob :	650
Net weight (kg) :	5.356
Type of control :	mechanical
Number of speed settings :	2-stage_Intensive
Maximum output air extraction (m <sup>3</sup> /h) :	170
Boost position output recirculating (m <sup>3</sup> /h) :	240.0
Boost position air extraction (m <sup>3</sup> /h) :	250
Number of lights :	2
Noise level (dB(A) re 1 pW) :	55
Diameter of air outlet (mm) :	120
Grease filter material :	Not washable synthetic
EAN code :	4242002259536
Connection Rating (W) :	230
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Built-in

**Optional accessories**

- DHZ2100 : Stencil for cut. out paper grease filter  
 DHZ7304 : Accessories extractor hoods



4 242002 259536

## Serie | 2, canopy cooker hood, 53 cm DHL535BGB

**Canopy cooker hoods are designed to be fully integrated for more flexibility when planning your kitchen.**

---

### **Design**

- 53 cm wide
- For installation into the base of a wall cupboard

### **Features**

- Rocker switch control for extractor speeds and light
- 2 power levels & intensive setting
- 2 x halogen light 30W
- Paper grease filter

### **Performance/technical information**

- Suitable for ducted or recirculating operation
- Maximum extraction 250 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 55 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
  - Intensive: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)

### **Optional accessories**

- Charcoal odour filter DHZ7304
- Paper grease filter DHZ2100