

**Serie | 8, island cooker hood, 90 cm,  
Stainless steel  
DIB091K50B**

A



**Stylish island chimney hoods perfectly complement island hob installations.**

- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.
- **LED illumination:** put your food in the spotlight.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.
- **LED illumination:** put your food in the spotlight.

**Technical Data**

Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	698-878/698-998
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	30.757
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m <sup>3</sup> /h) :	620
Boost position output recirculating (m <sup>3</sup> /h) :	470.0
Boost position air extraction (m <sup>3</sup> /h) :	850
Number of lights :	4
Noise level (dB(A) re 1 pW) :	62
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002811949
Connection Rating (W) :	272
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation typology :	Island

**Optional accessories**

- DHZ1231 : Adapter for roof inclination left/right
- DHZ1241 : Adapter for roof inclination front/back
- DHZ1246 : Chimney extension 1100 mm
- DHZ1256 : Chimney extension 1600 mm
- DHZ5385 : Standard recirculation kit
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6230 : CleanAir Recirculation Kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



4 242002 811949

## Serie | 8, island cooker hood, 90 cm, Stainless steel DIB091K50B

**Stylish island chimney hoods perfectly  
complement island hob installations.**

### Key Information

- Electronic control via TouchControl
- EcoSensor

### Design

- Designed for ceiling mounted installation
- 90 cm wide
- Brushed steel
- Inner frame

### Features

- TouchControl with lightline
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Automatic after running (10 min)
- Rim ventilation
- Additional noise reduction insulation
- 4 x LED lights
- Softlight dimmer function
- Dimmer function
- 3 metal grease filter cassettes
- Filter cover stainless steel, Removable metal grease filters
- Saturation indicator for metal and charcoal filter
- Filter saturation indicator

### Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm: max. Normal use 620 m<sup>3</sup>/h Intensive 850 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591: max. normal use 620 m<sup>3</sup>/h, intensive 850 m<sup>3</sup>/h
- Power rating: 272 W
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 62 dB(A) re 1 pW Intensive: 69 dB(A) re 1 pW
- Noise max. Normal Level: 62 dB\*
- Average Energy Consumption: 46.7 kWh/year\*
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 900 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 900 x 600 mm
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)
- Light Intensity: 888 lux
- Colour Temperature: 3500 K
- Efficient BLDC-technology

### Accessories

- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

\* In accordance with the EU-Regulation No 65/2014