

**wall-mounted cooker hood, 70 cm,
clear glass
DWA07E650B**



Optional accessories

DHZ1225 : Chimney extension 1000 mm
 DHZ1235 : Chimney extension 1500 mm
 DHZ5326 : Active carbon filter
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6200 : CleanAir Recirculation Kit

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 650 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

Technical Data

| | |
|---|--------------------|
| Color chimney : | Stainless steel |
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 582-902/582-1012 |
| Height of product, without chimney (mm) : | 52 |
| Minimum distance above an electric hob : | 550 |
| Minimum distance above a gas hob : | 650 |
| Net weight (kg) : | 17.770 |
| Type of control : | Electronic |
| Boost position output recirculating (m ³ /h) : | 380 |
| Maximum output recirculating air (m ³ /h) : | 280 |
| Boost position air extraction (m ³ /h) : | 650 |
| Number of lights : | 2 |
| Diameter of air outlet (mm) : | 120 / 150 |
| Grease filter material : | Washable aluminium |
| EAN code : | 4242002683690 |
| Connection Rating (W) : | 250 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50 |
| Plug type : | GB plug |
| Installation typology : | Wall-mounted |



**wall-mounted cooker hood, 70 cm, clear
glass
DWA07E650B**

**Wall mounted chimney hoods add style and
sophistication to the kitchen and give you
complete freedom in your kitchen planning.**

Key Information

- Electronic control
- Electronic power level display

Design

- Designed for wall mounted installation
- Brushed steel

Features

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- 2 x 20W low energy halogen lights
- 1 metal grease filter cassette

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 430 m³/h
Intensive 650 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at
maximum normal setting: extraction rate: 57 dB (A) re 1pW
(43 dB (A) re 20 μ Pa sound pressure)
- Extractor hose 120mm

Accessories

- Recirculating kit DHZ5325
- Dimensions recirculating with CleanAir module (HxWxD):
654 x 700 x 540 mm - mounting with outer chimney
774-1104 x 700 x 540 mm - mounting with telescopic chimney

wall-mounted cooker hood, 70 cm, clear glass
DWA07E650B

