

**wall-mounted cooker hood, 70 cm,
clear glass
DWA07W450B**



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 430 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-902/582-1012
Height of product, without chimney (mm) :	52
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	17.720
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	420
Maximum output recirculating air (m ³ /h) :	260
Number of lights :	2
Noise level (dB(A) re 1 pW) :	64
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002624983
Connection Rating (W) :	226
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted

Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5326 : Active carbon filter
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit



4 242002 624983

**wall-mounted cooker hood, 70 cm, clear
glass
DWA07W450B**

**Wall mounted chimney hoods add style and
sophistication to the kitchen and give you
complete freedom in your kitchen planning.**

Design

- 70 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel

Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x halogen bulbs
- 1 metal grease filter cassette

Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 430 m³/h
 - Intensive NO_FEATURE m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
 - Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 μ Pa sound pressure)
 - Intensive: NO_FEATURE dB(A) re 1 pW (NO_FEATURE dB(A) re 20 μ Pa sound pressure)
- Extractor hose 120mm
- Recirculating kit DHZ5325
- Dimensions recirculating with CleanAir module (HxWxD):
 - 654 x 700 x 540 mm - mounting with outer chimney
 - 774-1104 x 700 x 540 mm - mounting with telescopic chimney

**wall-mounted cooker hood, 70 cm, clear glass
DWA07W450B**

