

**Serie | 4**
**Classixx**  
**Box style hood**  
**DWB067A50B Brushed steel**

**A+**
**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 680 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	14.424
Type of control :	Electronic
Maximum output air extraction (m <sup>3</sup> /h) :	430
Boost position output recirculating (m <sup>3</sup> /h) :	360
Maximum output recirculating air (m <sup>3</sup> /h) :	300
Boost position air extraction (m <sup>3</sup> /h) :	680
Number of lights :	2
Noise level (dB(A) re 1 pW) :	58
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002779362
Connection Rating (W) :	136
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted


**Optional accessories**

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5326 : Active carbon filter
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative



## Serie | 4 Hoods

### Classixx

#### Box style hood

#### DWB067A50B Brushed steel

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

---

#### Key features

- Electronic control

#### Design

- 60 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

#### Features

- Soft touch button control, illuminated buttons
- 3 power levels & intensive setting
- Automatic intensive revert
- LED lights
- 2 metal grease filter cassettes

#### Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
  - max. Normal use 430 m<sup>3</sup>/h
  - Intensive 680 m<sup>3</sup>/h
- Maximum extraction rate 680 m<sup>3</sup>/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting; extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20  $\mu$ Pa sound pressure)