

**wall-mounted cooker hood, 60 cm,
Stainless steel
DWB06W450B**



Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-894/582-1004
Height of product, without chimney (mm) :	60
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	14.924
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m3/h) :	420
Maximum output recirculating air (m3/h) :	260
Number of lights :	2
Noise level (dB(A) re 1 pW) :	62
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002624846
Connection Rating (W) :	226
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted



Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5326 : Standard odor filter (replacement)
- DHZ6550 : Brushed steel back panel
- DHZ6551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit

wall-mounted cooker hood, 60 cm, Stainless steel DWB06W450B

Design

- 60 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x halogen bulbs
- 2 metal grease filter cassettes

Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 430 m³/h
 - Intensive NO_FEATURE m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 μ Pa sound pressure)
 - Intensive: NO_FEATURE dB(A) re 1 pW (NO_FEATURE dB(A) re 20 μ Pa sound pressure)
- Extractor hose 120mm
- Recirculating kit DHZ5325

Optional accessories

- Dimensions recirculating with CleanAir module (HxWxD):
 - 654 x 600 x 500 mm - mounting with outer chimney
 - 774-1104 x 600 x 500 mm - mounting with telescopic chimney

