

Serie | 4
**Classixx
Box style hood
DWB097A50B Brushed steel**
A+

Optional accessories

DHZ1223 : Chimney extension 1000 mm
 DHZ1233 : Chimney extension 1500 mm
 DHZ5345 : Recirculating kit
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6240 : CleanAir Recirculation Kit
 DZZ0XX0P0 : CleanAir act.carbon filter regenerative

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 730 m³/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 41 dB.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	18.251
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	460
Boost position output recirculating (m ³ /h) :	430
Maximum output recirculating air (m ³ /h) :	350
Boost position air extraction (m ³ /h) :	730
Number of lights :	3
Noise level (dB(A) re 1 pW) :	55
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002778440
Connection Rating (W) :	139
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation typology :	Wall-mounted



Serie | 4 Hoods

Classixx

Box style hood

DWB097A50B Brushed steel

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key features

- Electronic control
- Electronic power level display

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

Features

- Soft touch button control, illuminated buttons
- 3 power levels & intensive setting
- Automatic intensive revert
- LED lights
- Additional noise reduction insulation
- 3 metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 460 m³/h
Intensive 730 m³/h
- Maximum extraction rate 730 m³/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 55 dB (A) re 1pW
(41 dB (A) re 20 μ Pa sound pressure)