

**wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB099752B**



**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	687/687
Height of product, without chimney (mm) :	73
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	32.889
Type of control :	Electronic
Boost position output recirculating (m <sup>3</sup> /h) :	590
Maximum output recirculating air (m <sup>3</sup> /h) :	450
Boost position air extraction (m <sup>3</sup> /h) :	770
Number of lights :	4
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002541648
Connection Rating (W) :	317
Voltage (V) :	220-230
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted



4 242002 541648

## wall-mounted cooker hood, 90 cm, Stainless steel DWB099752B

---

### Key Information

- Electronic control
- Rim ventilation
- Grease and charcoal filter saturation indicators

### Design

- 90 cm wide
- Designed for wall mounted installation
- Brushed steel canopy and chimney section

### Features

- Metal touch controls
- 3 power levels & intensive setting
- Automatic intensive revert
- 4 x 20W low energy halogen lights
- Softlight dimmer function
- Dimmer function
- Automatic 10 minutes after running
- 
- 2 metal grease filter cassettes

### Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 550 m<sup>3</sup>/h  
Intensive 770 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13  
exhaust air:  
Max. normal use: 56 dB(A) re 1 pW (42 dB(A) re 20 µPa sound pressure)  
Intensive: 64 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Extractor hose 120mm
- Noise level according to EN 60704-3 und EN 60704-2-13  
Recirculating rate:  
Max. normal use: 63 dB(A) re 1 pW (49 dB(A) re 20 µPa sound pressure)  
Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa spund pressure)

### Optional accessories

- Decor panel premium black DSZ0660
- Recirculating kit DSZ5100
- Unique L-desing with mood lighting