

Serie | 6
**Exxcel
Angled chimney hood
DWK098E51B Brushed steel**

A
Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 730 m³/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-920/582-1030
Height of product, without chimney (mm) :	387
Minimum distance above an electric hob :	400
Minimum distance above a gas hob :	500
Net weight (kg) :	24.059
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	410
Boost position output recirculating (m ³ /h) :	380
Maximum output recirculating air (m ³ /h) :	310
Boost position air extraction (m ³ /h) :	730
Number of lights :	2
Noise level (dB(A) re 1 pW) :	58
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002778358
Connection Rating (W) :	166
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation typology :	Wall-mounted


Optional accessories

DHZ1225 : Chimney extension 1000 mm
 DHZ1235 : Chimney extension 1500 mm
 DHZ5326 : Active carbon filter
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6200 : CleanAir Recirculation Kit
 DZZ0XX0P0 : CleanAir act.carbon filter regenerative



Serie | 6 Hoods

Exxcel

Angled chimney hood DWK098E51B Brushed steel

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key features

- Electronic control
- Electronic power level display
- Charcoal filter saturation indicator

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

Features

- Soft touch button control for extractor speeds and light
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- LED lights
- Softlight dimmer function
- Florescent mood lighting
- 2 metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 410 m³/h
Intensive 730 m³/h
- Maximum extraction rate 730 m³/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at
maximum normal setting: extraction rate: 58 dB (A) re 1pW
(44 dB (A) re 20 μ Pa sound pressure)

Serie | 6 Hoods

Exxcel

Angled chimney hood
DWK098E51B Brushed steel

