

**wall-mounted cooker hood, 90 cm,
clear glass white printed
DWK09E820B**



Optional accessories

DHZ1225 : Chimney extension 1000 mm
 DHZ1235 : Chimney extension 1500 mm
 DHZ5326 : Standard odor filter (replacement)
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6200 : CleanAir Recirculation Kit



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 700 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-920/582-1030
Height of product, without chimney (mm) :	387
Minimum distance above an electric hob :	400
Minimum distance above a gas hob :	500
Net weight (kg) :	27.334
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	500
Boost position output recirculating (m ³ /h) :	380
Maximum output recirculating air (m ³ /h) :	330
Boost position air extraction (m ³ /h) :	700
Number of lights :	2
Noise level (dB(A) re 1 pW) :	61
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242002628110
Connection Rating (W) :	300
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted



**wall-mounted cooker hood, 90 cm, clear
glass white printed
DWK09E820B**

**Wall mounted chimney hoods add style and
sophistication to the kitchen and give you
complete freedom in your kitchen planning.**

Key Information

- Electronic control
- Electronic power level display

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- White

Features

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- 2 x 20W low energy halogen lights
- 2 metal grease filter cassettes

Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 510 m³/h
Intensive 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 μ Pa sound
pressure)
Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 μ Pa sound
pressure)
- Intensive: 68 dB (A) re 1 pW (54 dB (A) re 20 μ Pa sound
pressure)
- Extractor hose 120mm
- Recirculating kit DHZ5325
- Dimensions recirculating with CleanAir module (HxWxD):
853 x 900 x 441 mm - mounting with outer chimney
973-1303 x 900 x 441 mm - mounting with telescopic chimney

**wall-mounted cooker hood, 90 cm, clear
glass white printed
DWK09E820B**

