

**wall-mounted cooker hood, 90 cm,  
clear glass black printed  
DWK09M760B**



**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 700 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 5 min. burst to clear strong odours and then reverts back to the normal setting.

**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	553-981/553-981
Height of product, without chimney (mm) :	506
Minimum distance above an electric hob :	450
Minimum distance above a gas hob :	550
Net weight (kg) :	27.362
Type of control :	Electronic
Maximum output air extraction (m <sup>3</sup> /h) :	610
Boost position output recirculating (m <sup>3</sup> /h) :	380
Maximum output recirculating air (m <sup>3</sup> /h) :	360
Boost position air extraction (m <sup>3</sup> /h) :	700
Number of lights :	2
Noise level (dB(A) re 1 pW) :	64
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002702360
Connection Rating (W) :	315
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted



**Optional accessories**

DHZ5595 : Recirculating kit



4 242002 702360

**wall-mounted cooker hood, 90 cm, clear  
glass black printed  
DWK09M760B**

**Wall mounted chimney hoods add style and  
sophistication to the kitchen and give you  
complete freedom in your kitchen planning.**

---

**Key Information**

- Electronic control
- Electronic power level display
- Rim ventilation
- Grease and charcoal filter saturation indicators

**Design**

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Black

**Features**

- TouchControl for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- LED lights
- 2 x 20W low energy halogen lights
- Automatic 20 minutes after running
- 2 metal grease filter cassettes

**Performance/technical information**

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:  
max. Normal use 610 m<sup>3</sup>/h  
Intensive 700 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at  
maximum normal setting: extraction rate: 64 dB (A) re 1pW  
(50 dB (A) re 20  $\mu$ Pa sound pressure)
- Extractor hose 120mm

**Optional accessories**

- Recirculating kit

**wall-mounted cooker hood, 90 cm, clear  
glass black printed  
DWK09M760B**

