

Serie | 4

Classixx Chimney extractor hood DWW067A50B Brushed steel



A+



Optional accessories

DHZ1225 : Chimney extension 1000 mm
 DHZ1235 : Chimney extension 1500 mm
 DHZ5326 : Active carbon filter
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6200 : CleanAir Recirculation Kit
 DZZ0XX0P0 : CleanAir act.carbon filter regenerative

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 690 m³/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

| | |
|---|--------------------|
| Color chimney : | Stainless steel |
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 582-864/582-974 |
| Height of product, without chimney (mm) : | 90 |
| Minimum distance above an electric hob : | 550 |
| Minimum distance above a gas hob : | 650 |
| Net weight (kg) : | 14.824 |
| Type of control : | Electronic |
| Maximum output air extraction (m ³ /h) : | 430 |
| Boost position output recirculating (m ³ /h) : | 360 |
| Maximum output recirculating air (m ³ /h) : | 300 |
| Boost position air extraction (m ³ /h) : | 680 |
| Number of lights : | 2 |
| Noise level (dB(A) re 1 pW) : | 58 |
| Diameter of air outlet (mm) : | 120 / 150 |
| Grease filter material : | Washable aluminium |
| EAN code : | 4242002779560 |
| Connection Rating (W) : | 136 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50; 60 |
| Plug type : | GB plug |
| Installation typology : | Wall-mounted |



Serie | 4 Hoods

Classixx

Chimney extractor hood DWW067A50B Brushed steel

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key features

- Electronic control

Design

- 60 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

Features

- Soft touch button control, illuminated buttons
- 3 power levels & intensive setting
- Automatic intensive revert
- LED lights
- 2 metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 440 m³/h
Intensive 690 m³/h
- Maximum extraction rate 690 m³/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting; extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 μ Pa sound pressure)