

Serie | 2
DWW06W460B
Chimney extractor hood


Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 370 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- **Especially quiet:** high performance at just 53 dB.

Technical Data

Color chimney :	Black
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	553-730/573-730
Height of product, without chimney (mm) :	246
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	9.106
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	370
Maximum output recirculating air (m ³ /h) :	220
Number of lights :	2
Noise level (dB(A) re 1 pW) :	67
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002714233
Connection Rating (W) :	155
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation typology :	Wall-mounted

Optional accessories

- DHZ5275 : Recirculating kit
 DHZ5276 : Active carbon filter



4 242002 714233

Serie | 2 Hoods

DWW06W460B

Chimney extractor hood

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Design

- 60 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x halogen light 30W
- 2 metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 67 dB (A) re 1pW (53 dB (A) re 20 µPa sound pressure)
- Extractor hose 120mm
- Dimensions exhaust air (HxWxD): 799-976 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 799-976 x 600 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 270 lux
- Colour Temperature: 2700 K
- Energy Efficiency Class: E*
- Average Energy Consumption: 94.3 kWh/year*
- Blower Efficiency Class: E*
- Lighting Efficiency Class: G*
- Grease Filtering Efficiency Class: E*
- Noise max. Normal Level: 67 dB*

* In accordance with the EU-Regulation No 65/2014